

FHSD

FHSD MEZZANINE FLOOR Screw

FHSD is a ribbed head screw with a winged drill point suitable for wood to light gauge steel installations such as mezzanine floors.

Features

Benefits

- Wood to light gauge steel (2.0 to 4.0 mm thickness) application
- Winged drill point to help clear hole and penetrate steel
- Bit (BIT3SE) included
- Countersunk head with ribs


Material

- Yellow zinc dichromate finish

Applications

Suitable for:


- Mezzanine floors with a steel thickness of 2 to 4mm
- Use with Quik Drive tool QDHSD60 or QDHSD75

**YZP****INDOOR****EPD**

FHSD
FHSD MEZZANINE FLOOR Screw

Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d _h	d	l				
FHSD45E	9.9	5.4	45	23	750	1000-2500	QDHSD60E / QDHSD75E
FHSD64E		5.4	64	23	750	1000-2500	QDHSD60E / QDHSD75E

Capacities



References	Characteristic capacities [kN]								
	Withdrawal				Shear				Head pull-through (timber >15mm)
	Steel thickness [mm]				Steel thickness [mm]				
	2	3	4	5	2	3	4	5	
FHSD45E	3	6.2	7.2	10.6	2.1	2.1	1.6	1.9	1.3
FHSD64E	3	6.2	7.2	10.6	2.1	2.1	1.6	1.9	1.3

Winchester Road Cardinal Point Tamworth Staffordshire
 B78 3HG
 tel: +44 1827 255600
 fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
 Information presented on this document is the exclusive property of Simpson Strong-Tie®
 It is valid only when associated with products supplied by Simpson Strong-Tie®

FHSD
**FHSD MEZZANINE FLOOR
 Screw**



www.strongtie.co.uk