

## Technical data sheet

**SIMPSON**

**Strong-Tie**<sup>®</sup>

FSM

### Steel to Steel Screw

*Steel profile screws which is designed for joining reinforcement beams. The phosphated FSM is suited for fixing material up to 2x1.0 mm. The electrogalvanised FSM screw is suited for fixing material up to 2x2.0 mm.*

## Features

### Material

.

## Features

- Cross point head.
- Flat head.
- Drill point.
- Metal tapping thread.
- Phosphate coating option.
- Electrogalvanised coating option.

## Applications

### Suitable for

- Steel to steel.

### When to use


.



FSM  
Steel to Steel Screw

## Technical Data

### Product Dimensions



References	Item code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]					Qty/box
				d	l	d <sub>h</sub>	d <sub>1</sub>	bit	
FSM4.2X14	74398	1949893	53293452	4.2	14	7	2.9	PH2	500
FSM4.8X16	74397	1949892	53293433	4.8	16	8	4		500

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

FSM  
Steel to Steel Screw



[www.strongtie.co.uk](http://www.strongtie.co.uk)