

Technical data sheet

SIMPSON

Strong-Tie

HSB

Steel to Steel Screw - Drill Point

Self-drilling screw used to fix sheet metal to sheet metal, for example when joining ventilation to ductwork. Suitable for material up to 2x2.0 mm.

Features

Material

.

Features

- Cross point drive.
- Hex-washer head.
- Drill point.
- Metal tapping thread.
- Electrogalvanised coating.

Applications

Suitable For

- Steel to steel.

When to use



.



HSB
Steel to Steel Screw - Drill Point

Technical Data

Product Dimensions



References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]					Qty/box
				d	l	d _h	d ₁	bit	
HSB4.2X13	74392	1949887	53293312	4.2	13	8.5	3.6	1/4" + PH2	1000
HSB4.2X19	74393	1949888	53293323		19	8.5	3.6	1/4" + PH2	1000
HSB4.2X25	74394	1949889	53293338		25	8.5	3.6	1/4" + PH2	1000

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

HSB
Steel to Steel Screw - Drill
Point



www.strongtie.co.uk