

# Technical data sheet

**SIMPSON**

**Strong-Tie**

BRDC

## Grooved Countersunk Nail - Lacquered

*Nail with a countersunk head and grooved shank.  
Use indoors for fastening painted woodwork to  
timber or mouldings and other types of fine  
joinery.*



## Features

### Features

- Countersunk head.
- Grooved thread.
- Carbon steel - lacquered.

## Applications

### Suitable For

- Wood to wood.



BRDC  
Grooved Countersunk Nail - Lacquered

## Technical Data

Dimensions and drill holes



References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]		
				d	l	d <sub>h</sub>
BRDC1.4X25	74202	1950530	53291893	1.4	25	2.2
BRDC1.7X35	74203	1950531	53291904	1.7	35	2.7
BRDC1.7X40	74204	1950532	53291912	1.7	40	2.7
BRDC2.0X50	74205	1950533	53291923	2	50	3.2
BRDC2.3X60	74206	1950534	53291938	2.3	60	3.7

Winchester Road Cardinal Point Tamworth  
Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®  
Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

BRDC  
Grooved Countersunk Nail -  
Lacquered



[www.strongtie.co.uk](http://www.strongtie.co.uk)