

Technical data sheet

SIMPSON

Strong-Tie

BRDC

Grooved Countersunk Nail - Lacquered

*Nail with a countersunk head and grooved shank.
Use indoors for fastening painted woodwork to
timber or mouldings and other types of fine
joinery.*



Features

Features

- Countersunk head.
- Grooved thread.
- Carbon steel - lacquered.

Applications

Suitable For

- Wood to wood.



BRDC
Grooved Countersunk Nail - Lacquered

Technical Data

Dimensions and drill holes



| References | Item Code | Tun / DB nr. | NOB nr. | Fastener dimensions [mm] | | |
|------------|-----------|--------------|----------|--------------------------|----|----------------|
| | | | | d | l | d _h |
| BRDC1.4X25 | 74202 | 1950530 | 53291893 | 1.4 | 25 | 2.2 |
| BRDC1.7X35 | 74203 | 1950531 | 53291904 | 1.7 | 35 | 2.7 |
| BRDC1.7X40 | 74204 | 1950532 | 53291912 | | 40 | 2.7 |
| BRDC2.0X50 | 74205 | 1950533 | 53291923 | 2 | 50 | 3.2 |
| BRDC2.3X60 | 74206 | 1950534 | 53291938 | 2.3 | 60 | 3.7 |

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

BRDC
Grooved Countersunk Nail -
Lacquered



www.strongtie.co.uk