

Technical data sheet

SIMPSON

Strong-Tie

BRDEZ

Grooved Countersunk Nail - Electro Galvanised

Nail with a countersunk head and grooved shank for use indoors for fitting moulding or fixing hardwood and semi-hardwood boards to a wood base. Particularly suited for use where the head should be countersunk, so that the nail is concealed.

Features

Features

- Countersunk head.
- Grooved shank.
- Electro-galvanised coating.

Applications

Suitable For

- Wood to wood.



BRDEZ
Grooved Countersunk Nail - Electro Galvanised

Technical Data

Dimensions and drill holes



References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]		
				d	l	d _h
BRDEZ1.2X20	74196	1950524	53291836	1.2	20	1.9
BRDEZ1.4X25	74197	1950525	53291840	1.4	25	2.2
BRDEZ1.7X35	74198	1950526	53291855	1.7	35	2.7
BRDEZ1.7X40	74199	1950527	53291866	1.7	40	2.7
BRDEZ1.7X50	74200	1950528	53291874	1.7	50	2.7
BRDEZ2.0X50	74201	1950529	53291885	2	50	3.2

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

BRDEZ
Grooved Countersunk Nail -
Electro Galvanised



www.strongtie.co.uk