

## Technical data sheet

**SIMPSON**

**Strong-Tie**

BRDHG

### Grooved Countersunk Nail - Hot Dip Galvanised

*Nail with a countersunk head and grooved shank for use indoors for fitting moulding or fixing hardwood and semi-hardwood boards to a wood base.*

*Particularly suited for use where the head should be countersunk, so that the nail is concealed.*



## Features

### Features

- Countersunk head.
- Grooved shank.
- Hot dip galvanised coating.

## Applications

### Suitable For

- Wood to wood.



# Technical data sheet

**SIMPSON**

**Strong-Tie**

BRDHG

**Grooved Countersunk Nail - Hot Dip Galvanised**

## Technical Data

Dimensions and drill holes



References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]		
				d	l	d <sub>h</sub>
BRDHG1.7X35	74207	1950535	53291980	1.7	35	2.7
BRDHG1.7X40	74208	1950536	53291995		40	2.7
BRDHG2.0X50	74209	1950537	53292006	2	50	3.2
BRDHG2.3X60	74210	1950538	53292014	2.3	60	3.7
BRDHG2.8X75	74211	1950539	53292025	2.8	75	4.5

Winchester Road Cardinal Point Tamworth  
Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

BRDHG

**Grooved Countersunk Nail - Hot  
Dip Galvanised**



[www.strongtie.co.uk](http://www.strongtie.co.uk)

**SIMPSON**

**Strong-Tie**

2024-04-04