# **Technical data sheet**

#### POLY-GP General Purpose Resin Mortar

Chemical anchor for use in concrete and masonry. Specially formulated for light or medium duty fixing into hollow or solid base materials. Poly-GP300 is easy to use and fast curing, it enables good performance when used in applications such as fixing architectural steel work, cable trays, hand rails and gates.

# Features

#### Material

- Styrene free polyester
- Use with Simpson Strong-Tie threaded rod (LMAS) : galvanised steel and stainless A4-70

# Benefits

- Fast curing.
- Non-flammable.
- Low odour.
- Colour changes when cured.

# Applications

#### Header member

Hollow or solid masonry.

### For Use With

- Blinds
- Hinges
- Air conditioners
- Satellite Dishes
- Boilers









Fixation d'une cloture

SIMPSON Strong-Tie

#### POLY-GP General Purpose Resin Mortar

# **Technical Data**

Item Codes

References	Color	Content [ml]	Weight [kg]
Poly GP + LMAS M10*	-	-	-

Two nozzles are supplied with each cartridge. Downloadable Safety Data Sheet available from www.strongtie.eu

#### Performance Values

		Tension [Rds,N	] [kN]		Shear [Rds,V] [kN]					
References	Solid Brick	Autoclaved aerated concrete blocks	Hollow Brick	Hollow concrete block	Solid Brick	Autoclaved aerated concrete blocks	Hollow Brick	Hollow concrete block		
Poly GP + LMAS M10*	0.72	0.35	0.43	0.35	0.72	0.35	0.43	0.35		

Performance values are calculated from published data characteristic values in the ETA on which partial safety factors from ETA and a partial coefficient = 1.4 gf actions are applied. Service charges include the sealing position in the holder and is adhered to the method of installation. For hollow brackets unknown resistance, site of trials are needed (in accordance with ICASA recommendations for use by construction professionals for the construction of ankles tests on site).

# Technical data sheet

### POLY-GP General Purpose Resin Mortar



# Installation

**Curing Schedule** 

Temp of Support	-5°C	0°C	5°C	10°C	15°C	20°C	30°C
Working Time	25min	15min	12min	8min	7min	4min	2min
Curing Time	4h	3h	2h30	1h15	55min	30min	20min





# Solid Brick Installation

References	Ø drilling diameter [d0] [mm]	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [mm]	Minimum spacing - Smin [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - Cmin [mm]
Poly GP + LMAS M10*	12	12	85	15	6	80	200	50	100	50

#### POLY-GP **General Purpose Resin Mortar**

# Cellular Concrete

References	Ø drilling diameter [d0] [mm]	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [Nm]	Minimum spacing - Smin [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - Cmin [mm]
Poly GP + LMAS M10*	12	12	85	15	3	80	200	50	100	50

# Foundation Brick

References	Ø drilling diameter [d0] [mm]	Size of the Sieve	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [mm]	Minimum spacing - Smin [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - Cmin [mm]
Poly GP + LMAS M10*	16	16x85 ou 16x130	12	135	15	6	130	500	100	250	100

### Hollow Cinderblock

References	Ø drilling diameter [d0] [mm]	Size of the Sieve	Maximum diameter of hole in the fixture [df] [mm]	Depth of the drilling hole [h1] [mm]	Wrench Size [Sw]	Installation Torque [Tinst] [Nm]	Depth of the drilling hole [hef] [mm]	Characteristic spacing - S <sub>cr,N</sub> [mm]	Minimum spacing - Smin [mm]	Characteristic edge distance - C <sub>cr,N</sub> [mm]	Minimum edge distance - Cmin [mm]
Poly GP + LMAS M10*	16	16x130	12	135	15	6	130	500	100	250	100

POLY-GP

Mortar

**General Purpose Resin** 

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 fax: +44 1827 255616

Copyright by Simpson Strong-Tie® Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®

2025-06-27







the





www.strongtie.co.uk

SIMPSON Strong-Tie