

HS

Steel to Steel Screw - Sharp Point

Tapping screw used to fix sheet metal to sheet metal, for example when joining ventilation to ductwork. Suitable for material up to 2x1.0 mm.

Features

Material

.

Features

- Cross point drive.
- Hex-washer head.
- Sharp point.
- Twin thread.
- Electrogalvanised coating.

Applications

Suitable For

- Steel to steel.

When to use


.



HS
Steel to Steel Screw - Sharp Point

Technical Data

Product Dimensions



| References | Item Code | Tun / DB nr. | NOB nr. | Fastener dimensions [mm] | | | |
|------------|-----------|--------------|----------|--------------------------|----|----------------|------------|
| | | | | d | l | d _h | bit |
| HS4.2X13 | 74395 | 1949890 | 53293376 | 4.2 | 13 | 8.5 | 1/4" + PH2 |
| HS4.2X19 | 74396 | 1949891 | 53293380 | | 19 | 8.5 | 1/4" + PH2 |

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

HS
Steel to Steel Screw - Sharp
Point



www.strongtie.co.uk