

Technical data sheet

SIMPSON

Strong-Tie

TSB

Wood Fiber to Steel Screw - Drill Point

The TSB screw is ideally used indoors for fixing mouldings, OSB, chipboard and plywood to steel. It has a ribbed countersunk flat head which countersinks into the board to ensure a neat finish. The drill point allows the screw to fix boards to steel up to 2mm thick. The TSB screw has a PH2 recess and driver bits are included in every box.



YZP

INDOOR



Features

Material

Steel - yellow zinc coating

Features

- PH drive
- Ribbed countersunk head
- Drill point
- Twin thread
- Yellow zinc plated

Applications

Common Applications

- Timber to steel
- Wood fiber board to steel



TSB

Wood Fiber to Steel Screw - Drill Point

Technical Data

Product Dimensions



References	Item Code	Fastener Dimensions [mm]			Driver Bit	Box Quantity
		d	l	dh		
TSB3.9X28	74276	3.9	28	7	PH2	500

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

TSB

**Wood Fiber to Steel Screw -
Drill Point**



www.strongtie.co.uk

SIMPSON

Strong-Tie®

2024-05-04