

## Technical data sheet

**SIMPSON**

**Strong-Tie**

DSPROA4

### Hardwood Decking Screw - Stainless Steel A4

The DSPROA4 hardwood decking screw is a powerful fastening solution for hardwood decking such as IPE, Cumaru, Bankirai and others. Made from A4 stainless steel allows for the screw to be used in marine environments. The screw is designed to resist movement of the deck with a trim head for a neat, professional finish. The additional second thread helps pull the deck boards to the joist providing a more secure clamping effect.

Recommend pre-drilling with 4.0mm drill bit and pre countersinking close to the edge.

NEW

CE



A4  
INOX

AMBIANCE  
CORROSIVE



## Features

### Material

#### A4 stainless steel


### Features

- 6 lobe drive
- Double threaded
- Chisel point
- CE marked to EN14592

## Applications

### Common Applications

- Hardwood decking boards
- Hardwood to timber
- Outdoor applications
- Suitable for coastal environments



DSPROA4  
Hardwood Decking Screw - Stainless Steel A4

# Technical Data

## Product Dimensions



References	Item code	Dimensions [mm]					Bit	Box Quantity
		d	l	dh	lg1	lg2		
DSPROA45.5X60	74288	5.5	60	7	27.5	10.5	T-25	150

## Characteristic Capacities

References	Yield Moment $M_{y,k}$ [Nm]	Withdrawal Parameter $f_{ax,k}$ [N/mm <sup>2</sup> ]	Head Pull Through Parameter $f_{head,k}$ [N/mm <sup>2</sup> ]	Characteristic Tensile Capacity $f_{tens,k}$ [kN]	Torsional ratio
DSPROA45.5X60	7585	12.8	31.8	7.8	3.8

