Technical data sheet

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG



The framing nail is used for wood to wood constructions. The clipped head and the tight collation means that more nails can be loaded in the tools and the ring shank increases the withdrawal capacity.

Features

Advantages

- Clipped head (D-head)
- High withdrawal capacity
- Hot dip galvanised
- Annular ring thread
- Paper tape 34°

Applications

Support

• Framing wood to wood

















Technical data sheet

RSND34G





Technical Data

Product dimensions



References	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]					
neielelices	item code	DB III.	NUDD III.	d I		d _h	A _h	h _t	t _{fix}
RSND34G2.8X65	75762	2056109	55837755	2.8	65	5	19.6	1.1	48.2
RSND34G2.8X75	75763	2056110	55837766	2.0	75	5	19.6	1.1	58.2
RSND34G3.1X90	75764	2056111	55837740	3.1	88	5.3	22.1	1.2	69.4


Product characteristic properties

	Product characteristic properties								
References	Characteristic Yield Moment – M _{y,k} [M _{y.k}] [Nm]	Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [IV/mm²]	Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm²]	Characteristic tensile capacity - f _{tens,k} [f _{tens,k}] [kN]					
RSND34G2.8X65	3.2	9.3	22.9	3.1					
RSND34G2.8X75	3.2	9.3	22.9	3.1					
RSND34G3.1X90	4.7	8.6	-	3.1					

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG







It is valid only when associated with products supplied by Simpson Strong-Tie®