

CSA-Z Torx Head Connector Screw

CSA connector screw is developed for mounting of steel connectors to timber. The conical head secures fully contact to the connector which increases the transfer of force. A fixed connection with larger cross-bearing capacity than for standard screws is obtained. The torx helps to fix the screw during insertion.

Features

Material

- Steel quality: Carbon steel
- Corrosion protection: Impreg®+

Screwing

- 20 Torx bit.

Benefits

- Threading specific to wood allows easy and quick penetration into the wood.
- No splitting of the wood.


Applications

Suitable On

- **Supporting / Supported member:** solid wood, composite lumber, glued-laminated wood.

When to Use

- Joist hanger fastening.
- Angle brackets.
- Strips.



CSA skruer





QDBPC50E

CSA-Z
Torx Head Connector Screw

Technical Data

Product dimensions and characteristic capacities



References	DB nr.	NOBB nr.	Gunnebo art.nr	Fastener dimensions [mm]						Characteristic capacities - Timber C24 acc to ETA-04/0013 [kN]		Qty/box
				d	l	d _h	d ₁	l _g	bit	R _{lat,k}	R _{ax,k}	
CSA5.0X35Z	2056636	55836215	69836	5	35	8.3	3.15	29	T-20	2	2.1	250
CSA5.0X35Z-HV	2073841	55959101	-	5	35	8.3	3.15	29	T-20	2	2.1	1500
CSA5.0X40Z	2056635	55842375	69815	5	40	8.3	3.15	34	T-20	2.3	2.5	250
CSA5.0X40Z-HV	2073842	55959116	-	5	40	8.3	3.15	34	T-20	2.3	2.5	1500
CSA5.0X50Z	2316354	60053426	-	5	50	8.3	3.15	44	T-20	2.6	3.2	250

