

FBCB

Fibre Cement Screw, Drillpoint

FBCB screws are used in humid conditions both indoor and outdoor thanks to the impressive Impreg®+ coating. They are particularly suited for fixing fibre cement boards to steel. They are also suitable for timber to steel applications. The drill point means that the screws can be used to fix to steel up to 2mm thick. The ribbed countersunk flat head countersinks flush into the cement board/timber leaving a neat finish. FBCB screws are CE marked to EN14566 and have a PH2 drive recess.

Features

Material

Steel - Impreg®+ coating

Features

- CE marked to EN14566
- PH drive
- Ribbed countersunk head
- Drill point
- Twin thread
- Impreg®+ coating

Applications

Common Applications

- Cement board to steel
- Fibre cement board to steel
- Timber to steel



FBCB
Fibre Cement Screw, Drillpoint

Technical Data

Product Dimensions



References	Fastener Dimensions [mm]			Driver Bit	Box Quantity
	d	l	d _h		
FBCB3.9X25	3.9	25	6.8	PH2	250
FBCB3.9X35		35	6.8		

FBCB Collated Screws

References	Item code	DB nr.	NOBB nr.	Fastener Dimensions [mm]				Driver Bit	Box Quantity
				d	l	d _h	t _{fix}		
FBCB3.9X25 Collated	75721	2056068	55842201	3.9	25	6.8	15	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers
 Also available Quik Drive collated

