

Technical data sheet

SIMPSON

Strong-Tie

CLSZN

Wood Facade Screw - Impreg®+

The CLSZN is a double threaded screw suitable for use with timber cladding. The screw consists of type 17 point to prevent timber splitting on insertion and flat head with fiber lock technology which prevents moisture getting into the timber. The double thread ensures sufficient insertion, even in high density wood without the risk of spin-off. It also helps pull the cladding tight to the frame. The CLSZN screw has Impreg®+ coating and as therefore suitable for use in outdoor environments.



Features

Material

Steel - Impreg®+ coating

Features

- 6 lobe drive
- Flat head with fiber lock technology
- Double threaded
- Extreme ductility
- Type 17 point

Applications

Common Applications

- Cladding to timber
- Timber facades to timber



CLSZN

Wood Facade Screw - Impreg®+

Technical Data

Products dimensions



References	Item Code	Fastener dimensions [mm]						Box Quantity
		d	l	d _h	l _{g1}	l _{g2}	bit	
CLSZN4.8X48	-	4.8	48	8	26	18	T-20	250
CLSZN4.8X48 Bulk	-		48	8	26	18	T-20	1300
CLSZN4.8X65	-		65	8	26	22	T-20	250
CLSZN4.8X65 Bulk	-		65	8	26	22	T-20	750

