

HYS Hybrid Strut

The HYS hybrid strut is a versatile dual-application strut that has been specifically designed and tested for use as either a slide or rigid clip. Commonly used at the bottom of a steel beam to accommodate large standoff conditions, the HYS strut attaches LGS Studs to the main structure with screws.

Features

Description

The HYS hybrid strut is a versatile dual-application strut that has been specifically designed and tested for use as either a slide or fixed clip.



Commonly used at the bottom of a steel beam to accommodate large standoff conditions, the HYS strut attaches LGS Studs to the main structure with screws.

Key Features


- Available in 305mm and 381mm lengths.
- Ergonomically positioned slots minimise eccentric load and maximise capacity.
- Slide application allows up to 25mm of vertical moment in each direction when shouldered screws are used through the center of the slot.
- Simpson Strong-Tie® No-Equal® stamps mark the center of the slots to help ensure correct placement of shouldered screws

Material



Galvanised Mild Steel: 275g/m²




HYS12 Dimension Image





Slide Clip Installation




Slide Clip Screw Pattern S1 HYS fixed to Stud with 2 No Shouldered Screws (No screws required in small round holes in slide application)
Slide Clip Screw Pattern S3 HYS fixed to Stud with 3 No Shouldered Screws (No screws required in small round holes in slide application)




Fixed Clip Installation




Fixed Clip Screw Pattern F4 HYS fixed to Stud with 4 No Shouldered Screws (No screws required in slots in fixed application)
Fixed Clip Screw Pattern F6 HYS fixed to Stud with 6 No Shouldered Screws (No screws required in slots in fixed application)



HYS Clip to RSJ Screw pattern when installed with 2 No screws.



HYS Clip to RSJ Screw pattern when installed with 3 No screws.



HYS Clip to RSJ Screw pattern when installed with 4 No screws.


HYS
Hybrid Strut

Technical Data

Performance Values: HYS to RSJ Sections

Fasteners		Safe Working Loads [kN]	
Type	Qty	$R_{3,SWL} = R_{4,SWL}$	$R_{5,SWL} = R_{6,SWL}$
X1224D540	2	7.1	2.5
X1224D540	3	10.7	3.8
X1224D540	4	14.2	5.0

HYS - Product Dimensions




References	Hanger Dimensions [mm]					Holes Flange A		Holes Flange B	Maximum Standoff Distance [mm]			
	A	B	C	D	t	Ø4.8	Ø6.35x57 Slots	Ø4.8	Slide-Clip		Fixed-Clip	
									S ₂	S ₃	F ₄	F ₆
HYS15/68-KT25	89	38	381	13	2	12	6	12	251	219	203	203

Table Notes:

- Maximum standoff distance's are for two or three fasteners to primary structure

Slide-Clip - Performance Values - HYS to Stud (1.2mm Min. Stud Thickness)




References	Fasteners (Slide-Clip)		Screw Pattern ⁽²⁾															
	Stud	RSJ ⁽¹⁾	S ₂ (2 Screws per stud)							S ₃ (3 Screws per Stud)								
			Safe Working Loads [kN]				Characteristic Capacities [kN]			Safe Working Loads [kN]				Characteristic Capacities [kN]				
	Type	Type	$R_{1,SWL} = R_{2,SWL}$	$R_{3,SWL}$	$R_{4,SWL}$	$R_{5,SWL} = R_{6,SWL}$	$R_{1,K} = R_{2,K}$	$R_{3,K}$	$R_{4,K}$	$R_{5,K} = R_{6,K}$	$R_{1,SWL} = R_{2,SWL}$	$R_{3,SWL}$	$R_{4,SWL}$	$R_{5,SWL} = R_{6,SWL}$	$R_{1,K} = R_{2,K}$	$R_{3,K}$	$R_{4,K}$	$R_{5,K} = R_{6,K}$
HYS15/68-KT25	XLSH78B1414	X1224D540	0.7	3.8	2.8	-	1.1	6	6.4	-	0.7	5.7	5.6	-	1.1	9.1	9	-

Technical data sheet

SIMPSON

Strong-Tie


HYS
Hybrid Strut



Slide Clip
Installation

Slide-Clip - Performance Values - HYS to Stud (1.6mm Min. stud Thickness)

References	Fasteners (Slide-Clip)		Screw Pattern ⁽²⁾															
	Stud	RSJ ⁽¹⁾	S ₂ (2 Screws per Stud)							S ₃ (3 Screws per Stud)								
	Type	Type	Safe Working Loads [kN]				Characteristic Loads [kN]			Safe Working Loads [kN]				Characteristic Capacities [kN]				
			R _{1,SWL} = R _{2,SWL}	R _{3,SWL}	R _{4,SWL}	R _{5,SWL} = R _{6,SWL}	R _{1,K} = R _{2,K}	R _{3,K}	R _{4,K}	R _{5,K} = R _{6,K}	R _{1,SWL} = R _{2,SWL}	R _{3,SWL}	R _{4,SWL}	R _{5,SWL} = R _{6,SWL}	R _{1,K} = R _{2,K}	R _{3,K}	R _{4,K}	R _{5,K} = R _{6,K}
HYS15/68-KT25	XLSH78B1414	X1224D540	1.3	5.2	4.4	-	2.1	8.3	7.1	-	1.3	7.9	6.9	-	2.1	12.6	11	-



Fixed Clip
Installation

Fixed-Clip - Performance Values - HYS to Stud (1.2mm Min. Stud Thickness)


References	Fasteners (Fixed-Clip)		Screw Pattern ⁽²⁾															
	Stud	RSJ ⁽¹⁾	F ₄ (4 Screws per Stud)							F ₆ (6 Screws per Stud)								
	Type	Type	Safe Working Loads [kN]				Characteristic Capacities [kN]			Safe Working Loads [kN]				Characteristic Capacities [kN]				
			R _{1,SWL} = R _{2,SWL}	R _{3,SWL}	R _{4,SWL}	R _{5,SWL} = R _{6,SWL}	R _{1,K} = R _{2,K}	R _{3,K}	R _{4,K}	R _{5,K} = R _{6,K}	R _{1,SWL} = R _{2,SWL}	R _{3,SWL}	R _{4,SWL}	R _{5,SWL} = R _{6,SWL}	R _{1,K} = R _{2,K}	R _{3,K}	R _{4,K}	R _{5,K} = R _{6,K}
HYS15/68-KT25	XLSH78B1414	X1224D540	0.6	4.6	4.7	2	0.9	7.4	7.5	3.2	0.7	6.8	7	2	1.1	10.8	11.2	3.2

Technical data sheet



HYS
Hybrid Strut

Fixed-Clip - Performance Values - HYS to Stud (1.6mm Min. Stud Thickness)



References	Fasteners (Fixed-Clip)		Screw Pattern ⁽²⁾															
	Stud	RSJ ⁽¹⁾	F ₄ (4 Screws per Stud)								F ₆ (6 Screws per Stud)							
	Type	Type	Safe Working Loads [kN]				Characteristic Capacities [kN]				Safe Working Loads [kN]				Characteristic Capacities [kN]			
			R _{1,SWL} = R _{2,SWL}	R _{3,SWL}	R _{4,SWL}	R _{5,SWL} = R _{6,SWL}	R _{1,K} = R _{2,K}	R _{3,K}	R _{4,K}	R _{5,K} = R _{6,K}	R _{1,SWL} = R _{2,SWL}	R _{3,SWL}	R _{4,SWL}	R _{5,SWL} = R _{6,SWL}	R _{1,K} = R _{2,K}	R _{3,K}	R _{4,K}	R _{5,K} = R _{6,K}
HYS15/68- KT25	XLSH78B1414	X1224D540	0.9	9.4	9.6	2.5	1.4	15	15.4	4	1.7	13.7	11.7	2.5	2.7	22	18.7	4

Table Notes:

1. HYS Connector Loads are also limited by the RSJ Connection loads. Use the minimum tabulated values from the connector and RSJ tables as applicable.
2. See installation illustrations for fastener placement to stud framing.
3. Tabulated R₁ and R₂ loads are based on assembly tests with the load through the centerline of the stud.
4. Minimum stud width for fixed application is 150mm
5. XLSH78B1414 shouldered screw is supplied with the connectors

HYS Hybrid Strut

Installation



Installation

Slide Applications



- For installation as a slide connection, attach the HYS using XLSH78B1414 shouldered screws through the slotted holes (screws are supplied with the HYS)
- The precision-manufactured shouldered screws supplied with the HYS are designed to prevent over-driving and to ensure that the clip functions properly in the slide application.
- Fix to RSJ sections with X1224D540 screws (not supplied)
- Install quantity of fasteners in accordance to the number and pattern stated in the performance tables

Fixed Applications




- For installation as a fixed connection, attach the HYS using XLSH78B1414 shouldered screws through the round holes (screws are supplied with the HYS)
- Fix to RSJ sections with X1224D540 screws (not supplied)
- Install quantity of fasteners in accordance to the number and pattern stated in the performance tables




Slide Clip Screw Pattern S1 HYS fixed to Stud with 2 *Slide Clip Screw Pattern S3 HYS fixed to Stud with 3*
No Shouldered Screws (No screws required in small *No Shouldered Screws (No screws required in small*
round holes in slide application) *round holes in slide application)*




Fixed Clip Screw Pattern F4 HYS fixed to Stud with 4 *Fixed Clip Screw Pattern F6 HYS fixed to Stud with 6*
No Shouldered Screws (No screws required in *No Shouldered Screws (No screws required in*
slots in fixed application) *slots in fixed application)*




HYS Clip to RSJ Screw pattern when installed with 2 *HYS Clip to RSJ Screw pattern when installed with 3* *HYS Clip to RSJ Screw pattern when installed with 4*
No screws. *No screws.* *No screws.*




XLSH78B1414 Shouldered Screw - Used for
installation on Stud



X1224D540 - Used for installation on RSJ



Fixed Clip Installation



Slide Clip Installation

HYS
Hybrid Strut

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

HYS
Hybrid Strut

