

## Technical data sheet

**SIMPSON**

**Strong-Tie**

RCKW

### Kneewall Connector

The Simpson Strong-Tie® RCKW is a heavy duty rigid connector that has been developed to resist an overturning moment at the base of exterior kneewalls and parapets as well as interior partial height walls or overhead ribbon window conditions.

## Features

### Features

**The RCKW is a 1 or 2 part connector designed to resist an over-turning moment at the base of exterior knee-walls and parapets as well as interior partial height walls.**

**These connectors offer a unique large and small anchorage hole pattern that permits anchorage into both hot rolled steel and concrete.**

**If more rigidity is required, a stiffener (the RCKWS) can be added to nest into the RCKW clip; the screw and anchor holes line up making installation simple, with no need for pre drilling. The RCKW and the RCKWS are sold separately.**

**Key Features include:**

- Anchorage legs incorporate stiffened flanges, improving over-turning moment resistance
- Large diameter anchor holes accommodate 12 mm diameter fixings (LMAS stud with AT-HP Resin)
- Additional smaller diameter anchor holes allow for the attachment to hot rolled steel with X1224D540 self-drilling screws.

### Material

**Galvanised Mild Steel: 275 g/m<sup>2</sup>**




# Technical data sheet

## RCKW Kneewall Connector




## Technical Data

### Product Dimensions



RCKW3 & RCKW3S Dims


References	Hanger Dimensions [mm]							Holes Flange A		Holes Flange B			
	A	A <sub>1</sub>	B	C	D	D <sub>1</sub>	t	Ø4.8	Ø5.5	Ø6.7	Ø7.5	Ø14.3	Ø15.9
RCKW3	90	-	66	75	22	-	4.7	9	-	2	-	1	-
RCKW5.5	90	-	66	140	22	-	4.7	15	-	4	-	3	-
RCKW7.5	90	-	66	190	22	-	4.7	21	-	6	-	3	-
RCKW3S	-	38	56	75	-	19	4.7	-	3	-	2	-	1
RCKW5.5S	-	38	56	140	-	19	4.7	-	5	-	4	-	3



RCKW - Concrete Support

### Performance Values - 1.2mm LGS (Concrete)

References	Fasteners		Minimum Framing Member Depth [mm]	Screw Installation Pattern	Assembly Rotational Stiffness $\beta$ [Nm/Rad]	Connector Rotational Stiffness $\beta_c$ [Nm/Rad]	Moment $M_{R,SWL}$ [Nm]	Safe Working Loads [kN]				
	Flange A Stud	Flange B Concrete						Anchor Tension at $M_R$ Capacity		Tension $R_{2,SWL}$	Anchor Tension at $R_2$ Capacity	
	Qty (X1214D325)	Qty (M12 Anchor)						Concrete C20/25	Concrete C30/35		Concrete C20/25	Concrete C30/35
RCKW3	4	1	90	1	12767	12993	348	11.2	10.5	5.6	7.3	7.1
RCKW3+RCKW3S	9	1	90	2	18530	19772	476	17.5	15.4	11.5	19.6	16.7
RCKW5.5	6	1	150	3	36155	38189	706	11.2	10.9	4.7	5.8	5.7
RCKW5.5+RCKW5.5S	10	1	150	4	50843	55363	954	15.9	15.2	11.4	15.3	14.6
RCKW7.5	6	1	200	5	57622	60560	926	10.4	10.2	5.7	6.9	6.8
RCKW7.5+RCKW5.5S	10	1	200	6	66774	70390	1233	14.3	13.9	10	12.6	12.3




RCKW - Concrete Support

### Performance Values - 1.6mm LGS (Concrete)

References	Fasteners		Minimum Framing Member Depth [mm]	Screw Installation Pattern	Assembly Rotational Stiffness $\beta$ [Nm/Rad]	Connector Rotational Stiffness $\beta_c$ [Nm/Rad]	Moment $M_{R,SWL}$ [Nm]	Safe Working Loads [kN]				
	Flange A Stud	Flange B Concrete						Anchor Tension at $M_R$ Capacity		Tension $R_{2,SWL}$	Anchor Tension $R_2$ Capacity	
	Qty (X1214D325)	Qty (M12 Anchor)						Concrete C20/25	Concrete C30/35		Concrete C20/25	Concrete C30/35
RCKW3	4	1	90	1	14462	15479	489	18.3	16	8.2	11.8	11
RCKW3+RCKW3S	9	1	90	2	18530	19772	583	29.8	20.4	15.3	27.3	25.9
RCKW5.5	6	1	150	3	36155	38189	929	15.4	14.8	10.9	14.5	13.9
RCKW5.5+RCKW5.5S	10	1	150	4	52764	56718	1308	23.8	21.9	16.9	25.2	23.1
RCKW7.5	6	1	200	5	62594	64514	1288	15	14.6	9.6	12.1	11.8
RCKW7.5+RCKW5.5S	10	1	200	6	77847	81349	1587	19	18.3	11.7	14.9	14.5

# Technical data sheet


## RCKW Kneewall Connector



RCKW - Steel Support

### Performance Values - 1.2mm LGS (Structural Steel)

References	Fasteners		Minimum Framing Member Depth [mm]	Screw Installation Pattern	Assembly Rotational Stiffness $\beta$ [Nm/Rad]	Connector Rotational Stiffness $\beta_c$ [Nm/Rad]	Safe Working Loads [kN]			Characteristic Loads [kN]		
	Flange A Stud	Flange B Structural Steel					Moment $M_{R,SWL}$ [Nm]	Tension $R_{2,SWL}$	Shear $R_{4,SWL}$	Moment $M_{R,K}$ [Nm]	Tension $R_{2,K}$	Shear $R_{4,K}$
	Qty (X1214D325)	Qty (X1224D540)										
RCKW3	4	2	90	7	8281	8666	290	5.4	3.3	395	7.4	4.5
RCKW5.5	6	4	150	8	30798	32436	720	8.5	4.7	979	11.5	6.4
RCKW7.5	6	6	200	9	64579	68194	1084	8.7	5	1476	11.8	6.9



RCKW - Steel Support

### Performance Values - 1.6mm LGS (Structural Steel)

References	Fasteners		Minimum Framing Member Depth [mm]	Screw Installation Pattern	Assembly Rotational Stiffness $\beta$ [Nm/Rad]	Connector Rotational Stiffness $\beta_c$ [Nm/Rad]	Safe Working Loads [kN]			Characteristic Loads [kN]		
	Flange A Stud	Flange B Structural Steel					Moment $M_{R,SWL}$ [Nm]	Tension $R_{2,SWL}$	Shear $R_{4,SWL}$	Moment $M_{R,K}$ [Nm]	Tension $R_{2,K}$	Shear $R_{4,K}$
	Qty (X1214D325)	Qty (X1224D540)										
RCKW3	4	2	90	7	9859	10304	304	6.2	5	447	9.1	7.3
RCKW5.5	6	4	150	8	28911	30064	726	8.9	5.8	1070	13.1	8.5
RCKW7.5	6	6	200	9	78362	82656	1279	9.7	7.6	1883	14.3	11.2

#### Table Notes:


1. Tabulated values are based on framing members with track and stud of the same thickness and (1) Ø5.5mm Framing Screw into each stud flange unless otherwise noted.
2. Tabulated moment values correspond to connector strength without consideration of serviceability. designer must check out-of-plane deflections using tabulated Rotational Stiffness.
3. Tabulated Assembly Rotational Stiffness is applicable for walls at 950mm tall with corresponding framing member depth and thickness.
4. Tabulated Connector Rotational Stiffness may be used for any wall heights; the designer must consider member deflection due to bending in the stud member.
5. Anchor tension (T) is the force in the anchor, at the tabulated moment (M), or tension (F<sub>2</sub>) values.
6. The designer is responsible for anchor design / specification
7. The designer is responsible for structural steel design.
8. Anchor tension values may be interpolated
9. See illustrations for fastener pattern placement

## RCKW Kneewall Connector


### Installation

#### Installation


- Use all specified fasteners (see performance tables for fastener quantities and types)
- When using the RCKWS, secure the stiffener to the clip with the specified fasteners. Screws must extend through the connection with a minimum of three exposed threads.
- When installing onto concrete, the installation torque must be as published for the relevant anchor type and size
- When using the larger-diameter anchor holes, the bottom track must be predrilled or punched with a 20mm diameter hole.



RCKW3 Fastener Pattern 1  
- Concrete Application



RCKW3 with RCKW  
Fastener Pattern 2  
- Concrete Application




RCKW5.5 Fastener Pattern 3  
- Concrete Application

*RCKW3 Fastener Pattern 1 - Concrete Application*


*RCKW with RCKW3 Fastener Pattern 2 - Concrete Application*

*RCKW5.5 Fastener Pattern 3 - Concrete Application*




RCKW5.5 with RCKW5.5S  
Fastener Pattern 4  
- Concrete Application

*RCKW5.5 with RCKW5.5S Fastener Pattern 4 - Concrete Application*




RCKW7.5 Fastener Pattern 5  
- Concrete Application

*RCKW7.5 Fastener Pattern 5 - Concrete Application*




RCKW7.5 with RCKW5.5S  
Fastener Pattern 6  
- Concrete Application

*RCKW7.5 with RCKW5.5S Fastener Pattern 6 - Concrete Application*




RCKW3 Fastener Pattern 7  
- Structural Steel  
Application

*RCKW3 Fastener Pattern 7 - Structural Steel Application*



RCKW5 Fastener Pattern 8  
- Structural Steel  
Application


*RCKW5 Fastener Pattern 8 - Structural Steel Applications*




RCKW7 Fastener Pattern 9  
- Structural Steel  
Application

*RCKW7 Fastener Pattern 9 - Structural Steel Applications*


## RCKW Kneewall Connector




*RCKW - Concrete Support*




*RCKW - Concrete Installation*




*RCKW - Parapet Wall*



*RCKW - Steel Support*



*X1212D325 - LGS to LGS*



*X1224D540 - LGS to Rolled Steel*

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

RCKW  
Kneewall Connector

Copyright by Simpson Strong-Tie®  
Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

2024-04-30



[www.strongtie.co.uk](http://www.strongtie.co.uk)

SIMPSON

Strong-Tie®