## Technical data sheet

#### E1B Self-Drilling Screw

The E1B is a 6.1mm diameter self-drilling screw with a #3 drill point and hex washer head. The drill point allows the screw to penetrate the steel without the need for a pilot hole. Suitable for use with hold downs such as S/HDS. Driver bit not included.

### Features

Material

Steel - Clear zinc coating

#### Features

- 6.1mm x 25mm
- 3/8" hex washer head
- 12.2mm integral washer
- #3 drill point

## Applications

#### **Common Applications**

Recommended for use with certain Simpson Strong-Tie connectors for fixing to steel up to 8mm max.



#### E1B Self-Drilling Screw

# **Technical Data**

#### Product Dimensions

References	Fastener dimensions [mm]				TPI	Drill Point	Poy Quantity	
	Head	d <sub>w</sub>	d		151		Box Quantity	
E1B1414B/1	3/8" Hex	12.2	6.1	25	14	#3	1	
E1B1414B	3/8" Hex	12.2	6.1	25	14	#3	2500	

#### Performance Values

References	Performance Values [kN] / Member Thickness [mm]											
	Shear				Tension							
	Safe Working Loads [kN]		Characteristic Loads [kN]		Safe Working Loads [kN]		Characteristic Loads [kN]					
	1.2 [mm]	1.6 [mm]	1.2 [mm]	1.6 [mm]	1.2 [mm]	1.6 [mm]	1.2 [mm]	1.6 [mm]				
E1B1414B	1.3	2.7	2	4	0.6	1.1	0.9	1.7				

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 fax: +44 1827 255616

Copyright by Simpson Strong-Tie® Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®

E1B Self-Drilling Screw

2024-05-02



SIMPSON Strong-Tie

www.strongtie.co.uk