

SSBFHSD

Bi-Metal Timber to Steel Screw

The SSBFHSD screw is a bi-metal screw designed for timber to steel applications (1.2-2.4mm steel thickness). The bi-metal design consists of A4 stainless steel with a carbon steel winged drill point which is perfect for steel joist applications whilst still offering superior corrosion resistance. It has a countersunk ribbed flat head, fine thread and drill point with wings. The wings ream a hole larger in the timber and break off when they hit the steel allowing the timber to be pulled tight to the steel.

Features

Features

- Drives easily through 1.2–2.4 mm steel without predrilling
- A4 Stainless steel for severe corrosion resistance
- Winged design avoids sheet ride
- Zinc coating to avoid dissimilar metal corrosion
- Driver bit included (BIT2SE)

Material

Bi-metal - A4 stainless steel with carbon steel drill point

Applications

Applications

- Timber to steel decking
- Maximum recommended board thickness 28mm
- Recommended steel thickness 1.2–2.4mm



SSBFHSD
Bi-Metal Timber to Steel Screw

Technical Data

Product Dimensions



| References | Fastener dimensions [mm] | | | Max. board thickness [mm] | Max. steel thickness [mm] | Qty per strip | Qty per Box | Recommended RPM | Quik Drive Attachment |
|------------|--------------------------|----|----------------|---------------------------|---------------------------|---------------|-------------|-----------------|-----------------------|
| | d | l | d _h | | | | | | |
| SSBFHSD2SE | 4.9 | 50 | 8.5 | < 28mm | 1.2-2.4 | 30 | 1000 | 2500 | QDPROLDHG2 |

Winchester Road Cardinal Point Tamworth Staffordshire
 B78 3HG
 tel: +44 1827 255600
 fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
 Information presented on this document is the exclusive property of Simpson Strong-Tie®
 It is valid only when associated with products supplied by Simpson Strong-Tie®

SSBFHSD
**Bi-Metal Timber to Steel
 Screw**



www.strongtie.co.uk