

Technical data sheet

**FRUL
SIDER**

SIMPSON
StrongTie

X3 High Performance Long Plug

The X3 plugs in Ø8 and Ø10 mm versions in combination with countersunk / hexagon head screws are approved for multiple fixings in concrete and masonry.

Features

Material

Plug: nylon

Screw: white zinc plated steel

Benefits

- Extraordinary performance on all base materials.
- Up to 3 embedment depths
- Extreme versatility and significant reduction in installation time.
- Increased expansion
- Designed for facades and heavy carpentry.

Applications

Applications

- Ventilated facades
- Steel carpentry
- Wood carpentry

Suitable for

Non-cracked concrete

Solid brick

Honeycomb brick

- Cell like clay brick
- Lightweight honeycomb brick
- Hollow dense aggregate block
- Hollow light aggregate block
- Aerated concrete
- Solid stone



X3 High Performance Long Plug

Technical Data

Product Dimensions Countersunk TX Screw




Table "Product Dimensions Countersunk TX Screw" cannot be displayed : no references available.

Product Dimensions Hex-head Screw





Table "Product Dimensions Hex-head Screw" cannot be displayed : no references available.



Product Dimensions Large Rim Plug with Hex-head screw

Table "Product Dimensions Large Rim Plug with Hex-head screw" cannot be displayed : no references available.

Design capacities - single anchor - no edge distances





Table "Design capacities - single anchor - no edge distances" cannot be displayed : no references available.

Recommended capacities - single anchor - no edge distances

Table "Recommended capacities - single anchor - no edge distances" cannot be displayed :
no references available.

X3
High Performance Long Plug

Installation



Spacings and edge distances

Table "Spacings and edge distances" cannot be displayed : no references available.

Installation data

Table "Installation data" cannot be displayed : no references available.

