

Technical data sheet



QDHSD60E

Truck Bed and Mezzanine Floor Quik Drive Attachment

The QDHSD60E is designed to be used in conjunction with FHSD screws and TBG screws from 45mm to 64mm long. Use with FHSD screws to drill through steel thicknesses 3-5 mm for applications such as mezzanine floor installations. Use with TBG screws to drill through steel thicknesses 4-6 mm for truck bed/trailer installations.



Features

Material

- Manufactured containing PTFE
- No lubrication required

Benefits

- Connects easily with screw gun adapter or extension
- Possible 360° rotation of attachment on adapter or extension
- Self-lubricating material for long life and smooth operation
- Self-locking depth adjustment for consistent countersinking of screws
- Available as attachment only or with extension pole

Available Kits

QDHSD60E: Includes Quik Drive attachment, mandrel, driver bits, quiver and small carry case

QDHSD60KE: Includes Quik Drive attachment, mandrel, driver bits, quiver, large carry case and extension pole

Applications

Common Applications

Timber to steel applications:

- Mezzanine floor installations
- Truck bed/trailer installations

QDHSD60E

Truck Bed and Mezzanine Floor Quik Drive Attachment

Technical Data

Areas of use

QDHSD60KE
QDHSD60E

