

## Technical data sheet

**SIMPSON**

**Strong-Tie**

QDHSD60E

### Truck Bed and Mezzanine Floor Quik Drive Attachment

The QDHSD60E is designed to be used in conjunction with FHSD screws and TBG screws from 45mm to 64mm long. Use with FHSD screws to drill through steel thicknesses 3-5 mm for applications such as mezzanine floor installations. Use with TBG screws to drill through steel thicknesses 4-6 mm for truck bed/trailer installations.



## Features

### Material

- Manufactured containing PTFE
- No lubrication required

### Benefits

- Connects easily with screw gun adapter or extension
- Possible 360° rotation of attachment on adapter or extension
- Self-lubricating material for long life and smooth operation
- Self-locking depth adjustment for consistent countersinking of screws
- Available as attachment only or with extension pole

### Available Kits

**QDHSD60E: Includes Quik Drive attachment, mandrel, driver bits, quiver and small carry case**

**QDHSD60KE: Includes Quik Drive attachment, mandrel, driver bits, quiver, large carry case and extension pole**

## Applications

### Common Applications

#### Timber to steel applications:

- Mezzanine floor installations
- Truck bed/trailer installations

QDHSD60E

**Truck Bed and Mezzanine Floor Quik Drive Attachment**

## Technical Data

Areas of use

QDHSD60KE

QDHSD60E

Winchester Road Cardinal Point Tamworth  
Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

QDHSD60E

**Truck Bed and Mezzanine Floor Quik  
Drive Attachment**



[www.strongtie.co.uk](http://www.strongtie.co.uk)

**SIMPSON**

**Strong-Tie**

2024-04-26