

Technical data sheet

SIMPSON

Strong-Tie

DWF

Drywall to Steel Screw

The DWF screw has been designed to fix drywall to light gauge steel (0.6 - 0.9 mm thick). The sharp point allows for faster drilling whilst the bugle head provides a neat finish in the drywall. The DWF has a fine thread and is CE marked to EN14566. It has grey phosphate coating and is suitable for use indoors.

Features

Material

- Steel - Grey phosphate coating

Benefits

- CE marked to EN14566
- Bugle head
- Sharp point
- Fine thread
- PH2 driver bits included

Applications

Support

- Suitable for fixing to 0.6 - 0.9 mm steel

Common Applications

- Drywall to steel



DWF

Drywall to Steel Screw

Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d _h	d	l				
DWF3525PE	8.1	3.5	25	30	2500	2500 - 4000	QDPR051E / QD76KE
DWF3535PE		3.5	35	30	2500	2500 - 4000	QDPR051E / QD76KE
DWF3540PE		3.5	40	30	2500	2500 - 4000	QDPR051E / QD76KE
DWF3940PE		3.9	40	30	2500	2500 - 6000	QDPR051E / QD76KE

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

DWF
Drywall to Steel Screw



Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

2024-05-02

www.strongtie.co.uk