

Technical data sheet

SIMPSON

Strong-Tie

DWFSD

DRYWALL to Steel Screw

DWFSD is a self drilling screw with a fine thread, designed to fix drywall panels to steel of thicknesses 1.2 mm to 2.2 mm.

Features

Material

- Steel - yellow zinc plated

Benefits

- CE marked to EN14566
- Bugle haed
- Drill point
- Fine thread
- PH2 driver bits included (BIT2PE)

Applications

Support

- Suitable for fixing to 1.2 - 2.2 mm steel


Common Applications

- Fixing drywall board to steel



YZP

INDOOR



BIT2PE



DWFSD
DRYWALL to Steel Screw

Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d_h	d	l				
DWFSD32PE	8.2	3.5	32	30	2500	2500	QDPR051E / QD76KE
DWFSD41PE	8.2	3.5	41	30	2500	2500	QDPR051E / QD76KE

Winchester Road Cardinal Point Tamworth Staffordshire B78
 3HG
 tel: +44 1827 255600
 fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
 Information presented on this document is the exclusive property of Simpson Strong-Tie®
 It is valid only when associated with products supplied by Simpson Strong-Tie®

DWFSD
**DRYWALL to Steel
 Screw**



www.strongtie.co.uk