

Technical data sheet

SIMPSON

Strong-Tie

DWC

Drywall to Timber Screw

The DWC screw is designed for fixing drywall to timber. The screw features a sharp point, coarse thread and bugle head which provides a neat finish in the drywall. The DWC is CE marked to EN14566 and has a grey phosphate coating making it suitable for use indoors.

Features

Material

- Steel - Grey phosphate coating

Benefits

- CE marked to EN14566
- Bugle head
- Sharp point
- Coarse thread
- PH2 driver bits included (BIT2PE)

Applications

Support

- Suitable for fixing to solid wood, composite wood, glued laminate and OSB

Common Applications

- Plasterboard to timber




DWC

Drywall to Timber Screw

Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment	Weight [kg]
	d _h	d	l					
DWC3535PE	8.1	3.8	35	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWC3540PE	8.1	3.8	40	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWC3550PE	8.1	3.8	50	30	2000	2500 - 6000	QDPR051E / QD76KE	0.003
DWC3930PE	8.1	4	30	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWC3945PE	8.1	4	45	30	2000	2500 - 6000	QDPR051E / QD76KE	0.003
DWC3965PE	8.1	4	65	30	1500	2500 - 6000	QD76KE	0.005

