

# Technical data sheet

**SIMPSON**

**Strong-Tie**

DWC

## Drywall to Timber Screw

The DWC screw is designed for fixing drywall to timber. The screw features a sharp point, coarse thread and bugle head which provides a neat finish in the drywall. The DWC is CE marked to EN14566 and has a grey phosphate coating making it suitable for use indoors.

### Features

#### Material

- Steel - Grey phosphate coating

#### Benefits

- CE marked to EN14566
- Bugle head
- Sharp point
- Coarse thread
- PH2 driver bits included (BIT2PE)

### Applications

#### Support

- Suitable for fixing to solid wood, composite wood, glued laminate and OSB

### Common Applications

- Plasterboard to timber



DWC  
Drywall to Timber Screw

## Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	$d_h$	d	l				
DWC3525PE	8.1	3.8	25	30	2500	2500 - 6000	QDPR051E / QD76KE
DWC3535PE	8.1	3.8	35	30	2500	2500 - 6000	QDPR051E / QD76KE
DWC3540PE	8.1	3.8	40	30	2500	2500 - 6000	QDPR051E / QD76KE
DWC3545PE	8.1	3.8	45	30	2000	2500 - 6000	QDPR051E / QD76KE
DWC3550PE	8.1	3.8	50	30	2000	2500 - 6000	QDPR051E / QD76KE
DWC3925PE	8.1	4	25	30	2500	2500 - 6000	QDPR051E / QD76KE
DWC3930PE	8.1	4	30	30	2500	2500 - 6000	QDPR051E / QD76KE
DWC3945PE	8.1	4	45	30	2000	2500 - 6000	QDPR051E / QD76KE
DWC3965PE	8.1	4	65	30	1500	2500 - 6000	QD76KE

Winchester Road Cardinal Point Tamworth Staffordshire B78  
3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®  
Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

DWC  
Drywall to Timber  
Screw



[www.strongtie.co.uk](http://www.strongtie.co.uk)