

## Technical data sheet

**SIMPSON**

**Strong-Tie**

RDWF

### Dense Drywall Screw

The RDWF screw is recommended for fixing dense plasterboard to timber or light gauge steel from 0.6mm - 1.2mm thick. The reverse thread at the head end of the screw assists with countersinking the head into board. The screw has a reduced bugle head and high-low thread.

## Features

### Material

**Steel - Grey phosphate coating**

### Benefits

- CE marked to EN14566
- Reduced bugle head
- Sharp point
- High-low thread with reverse thread
- Driver bits included (BIT2PE)


## Applications

### Support

- For use with drywall or dense drywall board

### Common Applications

- Fixing drywall to timber
- Fixing drywall to steel up to 1.2mm thick



# Technical data sheet


**SIMPSON**

**Strong-Tie**

RDWF  
Dense Drywall Screw

## Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d <sub>h</sub>	d	l				
RDWF40BE	6.5	4.2	40	30	2500	2500 - 4000	QDPR051E / QD76KE

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®  
Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

RDWF  
Dense Drywall Screw



2024-05-01

[www.strongtie.co.uk](http://www.strongtie.co.uk)

**SIMPSON**

**Strong-Tie**