

Technical data sheet

SIMPSON

Strong-Tie

WSC

WSC WOOD FLOORING Screw, Coarse Thread

WSC is a screw with a sharp point and coarse thread, suitable for wood to wood applications such as flooring.

Features

Material

- Yellow zinc dichromate

Benefits

- Wood to wood applications
- Coarse thread
- WSC32E has Type 17 point and nibs under the head
- WSC38E has a sharp point without nibs under the head
- Bit (BIT2SE) included

Applications

Header member

- Solid wood, composite wood, glued laminated timber,
- Wood frame.

Applications

- Subfloor installation



YZP



Technical data sheet

SIMPSON

Strong-Tie

WSC

WSC WOOD FLOORING Screw, Coarse Thread

Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d _h	d	l				
WSC32E	8.5	4.3	32	30	2500	2500 - 4000	QDPR051E / QD76KE
WSC38E		4.3	38	30	2000	2500 - 4000	QDPR051E / QD76KE

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

WSC

**WSC WOOD FLOORING Screw,
Coarse Thread**



www.strongtie.co.uk

SIMPSON

Strong-Tie

2024-05-16