

WSC

**WSC WOOD FLOORING Screw, Coarse Thread**

WSC is a screw with a sharp point and coarse thread, suitable for wood to wood applications such as flooring.

## Features

### Material

- Yellow zinc dichromate

### Benefits

- Wood to wood applications
- Coarse thread
- WSC32E has Type 17 point and nibs under the head
- WSC38E has a sharp point without nibs under the head
- Bit (BIT2SE) included


## Applications

### Header member

- Solid wood, composite wood, glued laminated timber,
- Wood frame.

### Applications

- Subfloor installation





YZP



WSC  
**WSC WOOD FLOORING Screw, Coarse Thread**

## Technical Data

Product Dimensions UK



References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment	Weight [kg]
	d <sub>h</sub>	d	l					
WSC32E	8.5	4.3	32	30	2500	2500 - 4000	QDPR051E / QD76KE	0.003
WSC38E		4.3	38	30	2000	2500 - 4000	QDPR051E / QD76KE	0.003

Winchester Road Cardinal Point Tamworth  
 Staffordshire B78 3HG  
 tel: +44 1827 255600  
 fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®  
 It is valid only when associated with products supplied by Simpson Strong-Tie®

WSC  
**WSC WOOD FLOORING Screw,  
 Coarse Thread**



[www.strongtie.co.uk](http://www.strongtie.co.uk)