Technical data sheet

TBG
Truck Bed Screw

The TBG heavy duty truck bed screw is perfect for fixing timber to steel frames. It has a countersunk ribbed flat head, self tapping thread and drill point with wings. The wings ream a hole larger in the timber and break off when they hit the steel. This allows the timber to be pulled tight to the steel. Suitable for fixing to steel up to 5mm thick. TBG screws are suitable for all types of timber including Keruing hardwood and WISA plywood. They are also mechanically galvanised and so are suitable for outdoor use.

SC 3

YZP

OUTDOOR

BIT3SUE

Features

Material

- Steel - N2000® mechanically galvanised

Benefits

- Countersunk ribbed flat head for neat finish
- Suitable for outdoor use
- Self tapping thread
- Winged drill point to help clear hole and penetrate steel
- Driver bits included (BIT3SUE)

Applications

Support

- Used for fixing to steel or aluminium
- Maximum recommended steel thickness 5mm

Common Applications

- Truck beds and trailer floors
- Mezzanine floors
- Modular construction
- Mobile homes
- Caravans
- Boat building

Technical Data

Product Dimensions UK





References	Fastener dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d_h	d	l				
TBG645E	11.7	6.1	45	23	1000	1000 - 2500	QDHSD60E
TBG660E	11.7	6.1	60	23	750	1000 - 2500	QDHSD60E

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®