

## Technical data sheet

**SIMPSON**

**Strong-Tie**

CB3BLGHL

### Fibre Cement to Timber Screw

The CB3BLGHL is designed for fixing fibre cement board to timber. It has a flat countersunk head with ribs which enables the head of the screw to be easily countersunk into the fibre cement board ensuring a neat finish. The screw also has a sharp point and high-low thread design to provide a stronger grip in the timber.

CE



OUTDOOR



## Features

### Material

- Steel - C-3 mechanically galvanised coating

### Benefits

- CE Marked to EN14566
- Countersunk ribbed flat head for a neat finish
- Sharp point
- High-low thread for increased pull out resistance
- Driver bits included (BIT3SUE)

## Applications

### Support

- Used for fixing to timber

### Common Applications

- Fibre cement board to timber
- Cement board to timber



**BIT2SUE**



CB3BLGHL

**Fibre Cement to Timber Screw**

## Technical Data

Product Dimensions UK



References	Fastener Dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment
	d <sub>h</sub>	d	l				
CB3BLGHL32E	9.7	4.5	32	22	1500	2500	QDPROLDHG2
CB3BLGHL41E	9.7	4.5	41	22	1500	2500	QDPROLDHG2

Winchester Road Cardinal Point Tamworth Staffordshire  
B78 3HG  
tel: +44 1827 255600  
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®  
It is valid only when associated with products supplied by Simpson Strong-Tie®

CB3BLGHL  
**Fibre Cement to Timber  
Screw**

[www.strongtie.co.uk](http://www.strongtie.co.uk)**SIMPSON****Strong-Tie**

2024-02-22