

Technical data sheet

SIMPSON

Strong-Tie

CB3BLGHL

Fibre Cement to Timber Screw

The CB3BLGHL is designed for fixing fibre cement board to timber. It has a flat countersunk head with ribs which enables the head of the screw to be easily countersunk into the fibre cement board ensuring a neat finish. The screw also has a sharp point and high-low thread design to provide a stronger grip in the timber.



Features

Material

- Steel - C-3 mechanically galvanised coating

Benefits

- CE Marked to EN14566
- Countersunk ribbed flat head for a neat finish
- Sharp point
- High-low thread for increased pull out resistance
- Driver bits included (BIT3SUE)

Applications

Support

- Used for fixing to timber

Common Applications

- Fibre cement board to timber
- Cement board to timber





BIT2SUE



CB3BLGHL
Fibre Cement to Timber Screw

Technical Data

Product Dimensions UK



References	Fastener Dimensions [mm]			Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment	Weight [kg]
	d _h	d	l					
CB3BLGHL32E	9.7	4.5	32	22	1500	2500	QDPROLDHG2	5.4
CB3BLGHL41E		4.5	41	22	1500	2500	QDPROLDHG2	6.2

Winchester Road Cardinal Point Tamworth Staffordshire
 B78 3HG
 tel: +44 1827 255600
 fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
 It is valid only when associated with products supplied by Simpson Strong-Tie®

CB3BLGHL
**Fibre Cement to Timber
 Screw**



www.strongtie.co.uk