



A34

## Framing Anchor/Universal Framing Anchor

*The A34E anchor's exclusive bending slot allows instant, accurate bending on site for all two and three-way connections.*


*Balanced, completely reversible design allows the A34E to be used to secure a wide variety of connections.*



A34  
Framing Anchor/Universal Framing Anchor

## Technical Data

A34 / A35



References	Dimensions [mm]				Holes	
	A	B	C	t	Flange A	Flange B
					Ø4.1	Ø4.1
A34E	33	33	64	1.2	4	4

### A34E Performance Values

References	Number of Fasteners		Installation	Characteristic Capacity - Timber C24 <sup>(3)</sup> [kN]	Safe Working Load - Timber C16 [kN]											
	Flange A	Flange B			Long Term						Medium Term					
	N3.75x30	N3.75x30			R <sub>2,k</sub>	R <sub>1,SWL</sub>	R <sub>2,SWL</sub>	R <sub>3,SWL</sub>	R <sub>4,SWL</sub>	R <sub>5,SWL</sub>	R <sub>6,SWL</sub>	R <sub>1,SWL</sub>	R <sub>2,SWL</sub>	R <sub>3,SWL</sub>	R <sub>4,SWL</sub>	R <sub>5,SWL</sub>
A34E	4	4	1	-	1.3	1.3	-	1.1	-	-	1.5	1.5	-	1.2	-	

(3) Based upon 2 No brackets installed diagonally opposite to each other

