

IC Insulation Clip

The IC Insulation clip provides a quick and simple method of retaining rigid insulation within a timber frame panel, creating a controlled gap for services.

The IC saves time by allowing the insulation to be installed from the same side as the sheathing, which eliminates the need to turn the panel during construction.

Since it fixes to the stud via the speed prong feature - no nailing is required.

- Sizes to suit common stud widths.
- Multiple depths to suit common thickness of rigid insulation.
- Insulation installed same side as the sheathing - panel no longer needs to be turned during construction.
- No nails required, speed prong feature fixes into the stud.
- Split into two halves for single use around door and window openings, cripple studs and panel end studs.




Features

Material

- Pre-galvanised mild steel

Installation

- Make up the timber frame panel with the top and bottom rails and studs.
- Position IC clip on the studs and fix.
- Cut rigid insulation to size and push fit between the studs.
- Fix sheathing board onto the panel.



IC
Insulation Clip

Technical Data

Product Dimensions

References	Dimensions [mm]			
	A	B	C	t
IC71/38	38	71	18	0.55
IC81/38	38	81	18	0.55
IC91/38	38	91	18	0.55
IC101/38	38	101	18	0.55
IC106/38	38	106	18	0.55
IC111/38	38	111	18	0.55
IC121/38	38	121	18	0.55
IC136/38	38	136	18	0.55
IC165/38	38	165	18	0.55
IC176/38	38	176	18	0.55
IC71/45	45	71	18	0.55
IC91/45	45	91	18	0.55
IC101/45	45	101	18	0.55
IC106/45	45	106	18	0.55
IC111/45	45	111	18	0.55
IC121/45	45	121	18	0.55
IC165/45	45	165	18	0.55
IC176/45	45	176	18	0.55

