

Technical data sheet

SIMPSON

Strong-Tie

QDHSD75E

Truck Bed and Mezzanine Floor Quik Drive Attachment

Technical data sheet



QDHSD75E

Truck Bed and Mezzanine Floor Quik Drive Attachment

The QDHSD75E is designed to be used in conjunction with FHSD screws and TBG screws from 60mm to 75mm long. Use with FHSD screws to drill through steel thicknesses 3-5 mm for applications such as mezzanine floor installations. Use with TBG screws to drill through steel thicknesses 4-6 mm for truck bed/trailer installations.



Features

Material

- Manufactured containing PTFE
- No lubrication required

Benefits

- Connects easily with screw gun adapter or extension
- Possible 360° rotation of attachment on adapter or extension
- Self-lubricating material for long life and smooth operation
- Self-locking depth adjustment for consistent countersinking of screws
- Available as attachment only or with extension pole

Available Kits

QDHSD75E: Includes Quik Drive attachment, mandrel, driver bits, quiver and small carry case


QDHSD75KE: Includes Quik Drive attachment, mandrel, driver bits, quiver, large carry case and extension pole

Applications

Common Applications

Timber to steel applications:

- Mezzanine floor installations
- Truck bed/trailer installations



QDHSD75E

Truck Bed and Mezzanine Floor Quik Drive Attachment

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

QDHSD75E

**Truck Bed and Mezzanine Floor Quik
Drive Attachment**



www.strongtie.co.uk