Technical data sheet

DTHQ

Trim Head Decking Screw



The DTHQ is a trim head screw with coarse thread suitable for timber to timber applications such as decking. It has a Type 17 point which eliminates the need for pre-drilling and reduces the installation torque. The trim head provides a neat finish when countersunk into the timber and the Quik Guard® coating allows the screw to be used in external environments.

SC 3



Material

Steel - Quik Guard® coating


Benefits

- Type 17 point for faster, straighter drilling and reduced insertion torque
- · Counter sunk trim head for a neater finish
- Coarse thread
- Quik Guard coating prevents rust staining and prolonges life, even outdoors
- Driver bits included (BIT2SUE)

Applications

Common Applications

- Decking
- Timber to timber





Technical data sheet

DTHQ

Trim Head Decking Screw



Technical Data

Product Dimensions UK

References	Fastener dimensions [mm]				Qty per Strip	Qtv per Box	Recommended RPM	Quik Drive Attachment
	d _h	d	I	lg	Quy per ourp	QLY PEI DUX	Necommended Arivi	QUIK DIIVE ALLACIIIIIEIL
DTHQ51E	6.2	4.2	51	37	30	2000	2500	QDPR051E / QDPR064E / QD76KE
DTHQ64E		4.2	64	50	30	1500	2500	QDPR064E / QD76KE / QDPR076SKE
DTHQ76E		4.5	76	55	30	1000	2500	QD76KE / QDPR076SKE

Winchester Road Cardinal Point Tamworth Staffordshire B78

3HG tel: +44 1827 255600 fax: +44 1827 255616

Copyright by Simpson Strong-Tie®

Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®

DTHQ
Trim Head Decking
Screw



www.strongtie.co.uk

