### Technical data sheet

#### WST Wall Starter Tie

Screw in wall starter with nylon wall plug, WST provides lateral stability to brickwork or blockwork walls. Can be installed horizontally or at a 30° angle to the mortar joint.



# SIMPSON Strong-Tie

#### WST Wall Starter Tie

## **Technical Data**

#### WST Product Dimensions

| References | Dimensions [mm] |    |    |
|------------|-----------------|----|----|
|            | L               | ΤL | t  |
| WST135     | 135             | 38 | Ø5 |

#### WST Performance Values

| References | Characteristic Capacities [N]             |   |  |  |  |
|------------|---|---|--|--|--|
|            | Tension                                   |   | Shear                                    |  |  |
|            | Ultimate Declared<br>Tensile Strength [N] | Tensile Strength:<br>1mm Serviceability [N] | Ultuimate Declared<br>Shear Strength [N] | Shear Strength:<br>1 mm Serviceability [N] |  |
| WST135     | 1560                                      | 1450  | 1860                                     | 940  |  |

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 fax: +44 1827 255616

WST Wall Starter Tie





Copyright by Simpson Strong-Tie® Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®

2024-05-20 www.strongtie.co.uk