

Technical data sheet

SIMPSON

Strong-Tie

GK

Drywall to Wood or Steel Screw

Drywall screw is used indoors for fixing to timber battens and steel joists with a maximum thickness of 1.0 mm.

The duplex head prevents the paper on the plasterboard tearing on fitting.

Features

Material

.

Features

- Cross point head.
- Bugle Head.
- Sharp point
- High-low thread.
- Electrogalvanised coating.

Applications

Suitable For

- Drywall to timber.
- Drywall to steel.

When to use

.



Technical data sheet



SIMPSON

Strong-Tie®

GK
Drywall to Wood or Steel Screw

Technical Data

Product Dimensions



References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]						Weight [kg]
				d	l	d _h	d ₁	l _g	bit	
GK3.9X30	74299	1949829	53296085	3.9	30	8	3.2	25.5	PH2	0.002
GK3.9X30 Bulk	75336	2055693	55842424		30	8	3.2	25.5	PH2	0.002
GK3.9X40	74301	1949831	53296104		40	8	3.2	35.5	PH2	0.002
GK3.9X40 Bulk	75337	2055694	55842432		40	8	3.2	35.5	PH2	0.003
GK3.9X55	74303	1949833	53292574		55	8	3.2	50.5	PH2	0.003

GK Collated Screws

References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]						Qty/box
				d	l	d _h	d ₁	l _g	bit	
GK3.9X30 Collated	74296	1949826	53292377	3.9	30	8	3.2	25.5	PH2	1000
GK3.9X40 Collated	74297	1949827	53292381	3.9	40	8	3.2	35.5	PH2	1000
GK3.9X55 Collated	74298	1949828	53292396	3.9	55	8	3.2	50.5	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers

GK
Drywall to Wood or Steel Screw



SIMPSON
Strong-Tie®