

## Technical data sheet

**SIMPSON**

**Strong-Tie**

UGTS

### Exterior Sheathing to Steel or Wood Screw

*For fixing exterior sheathing to timber battens and steel joists of 1.0 mm maximum thickness. The head is suited to the requirements of fitting exterior plasterboard.*

## Features

### Material

.

### Features

- Cross point drive.
- Extended bugle head.
- Sharp point.
- High-low thread.
- Protec coating.

## Applications

### Suitable For

- Exterior drywall and wind board to wood.
- Exterior drywall and wind board to steel.

### When to use

.



## Technical data sheet



**SIMPSON****Strong-Tie®**

UGTS

**Exterior Sheathing to Steel or Wood Screw**

## Technical Data

### Product Dimensions



References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]				Weight [kg]
				d	l	d <sub>h</sub>	bit	
UGTS3.9X30	74307	1949835	53292593	3.9	30	8.9	PH2	0.001

### UGTS Collated Screws

References	Item Code	Tun / DB nr.	NOB nr.	Fastener dimensions [mm]				Qty/box
				d	l	d <sub>h</sub>	bit	
UGTS3.9X30 Collated	74305	1949834	53292604	3.9	30	8.9	PH2	1000

\* Flat tape collated for standard auto-feed screwdrivers

UGTS

**Exterior Sheathing to Steel or Wood Screw****SIMPSON****Strong-Tie®**