

TTUFS Countersunk Wood Screw - Electro Galvanised

*Suitable for interior use, the TTUFS screw has a serrated thread to reduce the resistance when driving.
It has a cut point which prevents cracking.
70mm or longer variants have an additional milling thread to further reduce the resistance.*

[Find it in the Solid Wood Application >](#)

Features

Material

-

Features

- 6 lobe drive.
- Flat head with facet.
- Type 17 point.
- Serrated thread.
- Electro galvanised.

Applications

Use on

-




Suitable For

- Wood to wood.



TTUFS Countersunk Wood Screw - Electro Galvanised

Product
Dimensions



References	Item Code	NOB nr.	Tun / DB nr.	Fastener dimensions [mm]						
				d	l	d _h	d _f	l _g	bit	
TTUFS4.0X40 FT	74429	53293966	1949924	4	40	8	2.5	35	T-20	
TTUFS4.0X45 PT	74430	53293974	1949925		45	8	2.5	29	T-20	
TTUFS4.0X50 PT	74431	53293985	1949926		50	8	2.5	30	T-20	
TTUFS4.0X60 PT	74432	53293993	1949927		60	8	2.5	35	T-20	
TTUFS4.0X70	74433	53294004	1949928		70	8	2.5	40	T-20	
TTUFS4.5X25	74434	53294012	1949929		4.5	25	8.4	2.8	20	T-20
TTUFS4.5X30	74435	53294023	1949930	30		8.4	2.8	25	T-20	
TTUFS4.5X35 FT	74436	53294038	1949931	35		8.4	2.8	30	T-20	
TTUFS4.5X40 FT	74437	53294042	1949932	40		8.4	2.8	35	T-20	
TTUFS4.5X45 PT	74438	53294057	1949933	45		8.4	2.8	29	T-20	
TTUFS4.5X50 PT	74439	53294061	1949935	50		8.4	2.8	30	T-20	
TTUFS4.5X60 PT	74440	53294076	1949936	60		8.4	2.8	35	T-20	
TTUFS4.5X70	74441	53294080	1949937	70		8.4	2.8	40	T-20	
TTUFS4.5X80	74442	53294095	1949938	80		8.4	2.8	50	T-20	
TTUFS5.0X40 FT	74374	53294133	1949942	5		40	9.5	3.1	35	T-25
TTUFS5.0X50 PT	74375	53294144	1949943			50	9.5	3.1	30	T-25
TTUFS5.0X60 PT	74376	53294152	1949944			60	9.5	3.1	35	T-25
TTUFS5.0X70	74377	53294163	1949945		70	9.5	3.1	40	T-25	
TTUFS5.0X80	74378	53294178	1949946		80	9.5	3.1	40	T-25	
TTUFS5.0X90	74379	53294182	1949947		90	9.5	3.1	45	T-25	
TTUFS5.0X90 Bulk	75500	55838213	2055855		90	9.5	3.1	45	T-25	
TTUFS5.0X100	74443	53294106	1949939		100	9.5	3.1	60	T-25	
TTUFS5.0X120	74372	53294114	1949940		120	9.5	3.1	60	T-25	
TTUFS6.0X60	74458	53294265	1949955		6	60	11.6	3.7	35	T-30
TTUFS6.0X70	74459	53294273	1949956	70		11.6	3.7	40	T-30	
TTUFS6.0X80	74460	53294284	1949957	80		11.6	3.7	40	T-30	
TTUFS6.0X90	74461	53294292	1949958	90		11.6	3.7	45	T-30	
TTUFS6.0X100	74380	53294197	1949948	100		11.6	3.7	60	T-30	
TTUFS6.0X120	74451	53294201	1949949	120		11.6	3.7	70	T-30	
TTUFS6.0X140	74452	53294216	1949950	140		11.6	3.7	70	T-30	
TTUFS6.0X160	74453	53294220	1949951	160		11.6	3.7	70	T-30	
TTUFS6.0X180	74454	53294235	1949952	180		11.6	3.7	70	T-30	

Diameters 3.0, 3.5 and 4.0 screws are not CE marked.

FT = Full Thread

PT = Partial Thread

PTM = Parial Thread with Milling Thread

TTUFS Countersunk Wood Screw - Electro Galvanised

Product characteristic properties

References	Characteristic Yield Moment - $M_{y,k}$ [Nmm]	Characteristic withdrawal parameter - $f_{ax,k,90^\circ}$ [N/mm ²]	Characteristic head pull-through parameter - $f_{head,k}$ [N/mm ²]	Characteristic tensile capacity - $f_{tens,k}$ [kN]
TTUFS4.5X25	4660	14.7	15.6	7.8
TTUFS4.5X30	4660	14.7	15.6	7.8
TTUFS4.5X35 FT	4660	14.7	15.6	7.8
TTUFS4.5X40 FT	4660	14.7	15.6	7.8
TTUFS4.5X45 PT	4660	14.7	15.6	7.8
TTUFS4.5X50 PT	4660	14.7	15.6	7.8
TTUFS4.5X60 PT	4660	14.7	15.6	7.8
TTUFS4.5X70	4660	14.7	15.6	7.8
TTUFS4.5X80	4660	14.7	15.6	7.8
TTUFS5.0X40 FT	6720	15	17.1	7.9
TTUFS5.0X50 PT	6720	15	17.1	7.9
TTUFS5.0X60 PT	6720	15	17.1	7.9
TTUFS5.0X70	6720	15	17.1	7.9
TTUFS5.0X80	6720	15	17.1	7.9
TTUFS5.0X90	6720	15	17.1	7.9
TTUFS5.0X90 Bulk	6720	15	17.1	7.9
TTUFS5.0X100	6720	15	17.1	7.9
TTUFS5.0X120	6720	15	17.1	7.9
TTUFS6.0X60	9500	12.5	16.6	11.1
TTUFS6.0X70	9500	12.5	16.6	11.1
TTUFS6.0X80	9500	12.5	16.6	11.1
TTUFS6.0X90	9500	12.5	16.6	11.1
TTUFS6.0X100	9500	12.5	16.6	11.1
TTUFS6.0X120	9500	12.5	16.6	11.1
TTUFS6.0X140	9500	12.5	16.6	11.1
TTUFS6.0X160	9500	12.5	16.6	11.1
TTUFS6.0X180	9500	12.5	16.6	11.1

Refer to relevant ITTR or ETA for more details

TTUFS
Countersunk Wood Screw - Electro Galvanised

