Technical data sheet

CSA-Z

Screws for Torx head connectors Impreg® +

CSA connector screw is developed for mounting of steel connectors to timber.
The conical head secures fully contact to the connector which increases the transfer of force. A fixed connection with larger cross-bearing capacity than for standard screws is obtained.
The torx helps to fix the screw during insertion.



CSA skruer

QDBPC50E

Features

Material

- Steel quality: Carbon steel
- Corrosion protection: Impreg®+

Screwing

- 20 Torx bit.

Benefits

- Threading specific to wood allows easy and quick penetration into the wood.
- No splitting of the wood.

Applications

When to Use

- Joist hanger fastening.
- Angle brackets.
- Strips.

Technical Data

Product dimensions and characteristic capacities





References	Fastener dimensions [mm]						Characteristic capacities - Timber C24 acc to ETA-04/0013 [kN]	
	d	l	d_h	d_1	l_g	bit	$R_{lat.k}$	$R_{ax.k}$
CSA5.0X35Z	5	35	8.3	3.15	29	T-20	2	2.1
CSA5.0X40Z	5	40	8.3	3.15	34	T-20	2.3	2.5
CSA5.0x50Z	5	50	8.3	3.15	44	T-20	2.6	3.2

Copyright by Simpson Strong-Tie®