

## Technical data sheet

**SIMPSON**

**Strong-Tie**

EGCM

### End Grain Connector (Medium Duty)

Suitable for solid timber and Glulam joists: EGCM is a two-piece system that provides a high-strength, hidden connection between timber members where the joist header or post is fastened into the end-grain of a carried joist. As the connector is concealed within the timbers, this method provides 30 minutes fire resistance. EGCM can be surface mounted or recess fitted. A routing template is available separately.

## Features

### Material

- Joist plate: 16mm aluminium
- Header plate: 16mm aluminium

### Features

- Concealed connection
- Provides up to 30 mins fire resistance
- Can be routed for flush installation, or surface mounted
- Can be pre-installed off-site for rapid assembly
- Each component easy to pair due to identical width and height
- Light weight aluminium for ease of handling

## Applications

### Suitable For

- Solid timber
- Glulam

### Use With

- Timber to timber connections as part of single or multi-storey construction projects

### Installation



- Mounting connectors EGCM is simplified by the use of a jig available on stock.
- The slot can be routed by using a Ø16mm cutter with Ø30mm washer.
- CAUTION: EGCM should not be used for an assembly with a negative slope.



## EGCM End Grain Connector (Medium Duty)

## Technical Data

### Product dimensions





EGCM recess fit onto Glulam timber (cross-section)

References	Joist Dimensions [mm]				Header Dimensions [mm]	Product Dimensions [mm]			Header Holes [mm]	Joist Holes [mm]	Weight [kg]
	Width	Height [mm]			Post Width	A	B	t	Ø6.5	Ø6.5	
		β=0°		-15°<β<90°							
		Min	Max								
EGCM90	75	*	*	*	125	90	50	16	6	7	0.17
EGCM150	75	*	*	*	125	150	50	16	11	12	0.28
EGCM210	75	*	*	*	125	210	50	16	18	15	0.4
EGCM270	75	*	*	*	125	270	50	16	21	18	0.52

\*Depends on CSFT screw length

### Product Characteristic capacities - Timber Beam to Timber Beam



EGCM recess fit onto solid timber (cross-section)

References	Product Characteristic Capacities - Timber Beam to Timber Beam													
	Fastener Qty		Characteristic Capacities - Timber C24 [kN]											
	Header	Joist	CSFT6.0x85							CSFT6.0x110				
			Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub>	R <sub>4,k</sub>	Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub>	R <sub>4,k</sub>
			Min	Max					Min	Max				
EGCM90	6	5 (7)	135	180	14.2	6.5	12.7	8.6	150	210	18.3	8.7	14	9.6
EGCM150	11	10 (12)	195	270	27.8	6.5	23.7	16.7	210	350	35.6	8.7	25.9	18.7
EGCM210	16	13 (15)	255	360	35.6	6.5	28.6	22.3	270	390	46	8.7	31.4	24.9
EGCM270	21	16 (18)	315	450	43.2	6.5	33	27.7	330	480	56.2	8.7	36.4	31


The quantities in brackets are the quantities of fixings in the supported beam plus the screws to prevent lifting. The top screws going from the joist par to the header must be installed to block the uplift.

# Technical data sheet




## EGCM End Grain Connector (Medium Duty)

### Product Characteristic Capacities - Timber Beam to Timber Post




EGCM surface fit onto solid timber post (cross-section)




References	Product Characteristic Capacities - Timber Beam to Timber Post													
	Fastener Qty		Characteristic capacities - Timber C24 [kN]											
	Header	Joist	CSFT6.0x85						CSFT6.0x110					
			Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub>	R <sub>4,k</sub>	Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub>	R <sub>4,k</sub>
			Min	Max					Min	Max				
EGCM90	6	5 (7)	135	180	14.2	6.5	12.7	8.6	150	210	18.3	8.7	14	9.6
EGCM150	11	10 (12)	195	270	27.8	6.5	23.7	16.7	210	350	31.6	8.7	25.9	18.7
EGCM210	16	13 (15)	255	360	35.6	6.5	28.6	22.3	270	390	41.1	8.7	31.4	24.9
EGCM270	21	16 (18)	315	450	43.2	6.5	33	27.7	330	480	56.2	8.7	36.4	31

The quantities in brackets are the quantities of fixings in the supported beam plus the screws to prevent lifting. The top screws going from the joist par to the header must be installed to block the uplift.

### Product Characteristic Capacities - Timber Beam to Wall Plate



EGCM recess fit onto Glulam timber (cross-section)



References	Product Characteristic Capacities - Timber Beam to Wall Plate															
	Fasteners				Characteristic Capacities - Timber C24 [kN]											
	Header [mm]		Joist		CSFT6.0x85						CSFT6.0x110					
	Type	Qty	Qty	Type	Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub>	R <sub>4,k</sub>	Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub>	R <sub>4,k</sub>
					Min	Max					Max	Min				
EGCM90	TTUFS5,0x50	6	CSFT	5 (7)	135	180	14.2	6.5	4	8.6	150	210	15.2	8.7	4	9.6
EGCM150	TTUFS5,0x50	11	CSFT	10 (12)	195	270	27.8	6.5	7.3	16.7	210	350	27.9	8.7	7.3	18.7
EGCM210	TTUFS5,0x50	16	CSFT	13 (15)	255	360	35.6	6.5	10.6	22.3	270	390	40.6	8.7	10.6	24.9
EGCM270	TTUFS5,0x50	21	CSFT	16 (18)	315	450	43.2	6.5	13.9	27.7	330	480	53.3	8.7	13.9	31

The quantities in brackets are the quantities of fixings in the supported beam plus the screws to prevent lifting. The top screws going from the joist par to the header must be installed to block the uplift.



# Technical data sheet

**SIMPSON**

**Strong-Tie**

EGCM

**End Grain Connector (Medium Duty)**



EGCM recess fit onto solid timber (cross-section)

DE - Product characteristic capacities - Timber beam to timber beam / post

References	Product Characteristic Capacities - Timber Beam to Timber Beam													
	Fastener Qty		Characteristic Capacities - Timber C24 [kN]											
	Header	Joist	CSFT6.0x85						CSFT6.0x110					
			Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub> - DE	R <sub>4,k</sub> - DE	Joist Height [mm]		R <sub>1,k</sub>	R <sub>2,k</sub>	R <sub>3,k</sub> - DE	R <sub>4,k</sub> - DE
			Min	Max					Min	Max				
EGCM90	6	5 (7)	135	180	14.2	6.5	*	8.6	150	210	18.3	8.7	*	9.6
EGCM150	11	10 (12)	195	270	27.8	6.5	*	16.7	210	350	31.6	8.7	*	18.2 / kmod
EGCM210	16	13 (15)	255	360	35.6	6.5	*	18.2 / kmod	270	390	41.1	8.7	*	18.2 / kmod
EGCM270	21	16 (18)	315	450	43.2	6.5	*	18.2 / kmod	330	480	56.2	8.7	*	18.2 / kmod

The quantities in brackets are the quantities of fixings in the supported beam plus the screws to prevent lifting. The top screws going from the joist par to the header / post must be installed to block the uplift.


EGCM

**End Grain Connector (Medium Duty)**


## Installation

### Fasteners


- On header, TTUFS Ø5mm according to ETA-21/0670 (for header <80mm) and CSFT Ø6mm screws.
- On joist, CSFT Ø6mm screws.




*EGCM recess fit onto solid timber*




*EGCM recess fit onto solid timber (cross-section)*




*EGCM surface fit onto solid timber*




*EGCM surface fit onto solid timber (cross-section)*




*EGCM surface fit onto solid timber post (cross-section)*




*EGCM surface fit onto Glulam timber*




*EGCM surface fit onto Glulam timber (cross-section)*



*EGCM recess fit onto Glulam timber*



*EGCM recess fit onto Glulam timber (cross-section)*



*EGCM surface fit onto Glulam post*

EGCM

**End Grain Connector (Medium Duty)**

