

Technical data sheet

CLR Plus SK Countersunk Concrete Screws

SIMPSON

Strong-Tie®

The countersunk head is often used when the screw must remain flush with the object to be fixed, for aesthetical reasons or to avoid interferences above it.




Applications

Material

- Electro-galvanized steel

Suitable on

- Cracked and uncracked concrete



Technical data sheet

SIMPSON**Strong-Tie®**

CLR Plus SK
Countersunk Concrete Screws

Technical Data

Product dimensions

References	Item code	Type [d x L]	Hole diameter	Fixing thickness for reduced embedment depth	Fixing thickness for standard embedment depth	Fixing thickness for increased embedment depth	Qty per box
CLR Plus SK 5x40	72107B0504000	5x40	5	5	-	-	100
CLR Plus SK 5x60	72107B0506000	5x60	5	25	-	-	100
CLR Plus SK 6x40	72107B0604000	6x40	6	5	-	-	100
CLR Plus SK 6x60	72107B0606000	6x60	6	25	20	5	100
CLR Plus SK 6x80	72107B0608000	6x80	6	45	40	25	100
CLR Plus SK 8x80	72107B0808000	8x80	8	35	25	15	50
CLR Plus SK 8x100	72107B0810000	8x100	8	55	45	35	50
CLR Plus SK 10x90	72107B1009000	10x90	10	35	15	5	50
CLR Plus SK 10x100	72107B1010000	10x100	10	45	25	15	50

CLR Plus SK
Countersunk Concrete Screws

**SIMPSON**
Strong-Tie®