

Technical data sheet

SIMPSON

Strong-Tie

DWF

Drywall to Steel Screw

The DWF screw has been designed to fix drywall to light gauge steel (0.6 - 0.9 mm thick). The sharp point allows for faster drilling whilst the bugle head provides a neat finish in the drywall. The DWF has a fine thread and is CE marked to EN14566. It has grey phosphate coating and is suitable for use indoors.

Features

Material

- Steel - Grey phosphate coating

Benefits

- CE marked to EN14566
- Bugle head
- Sharp point
- Fine thread
- PH2 driver bits included

Applications

Support

- Suitable for fixing to 0.6 - 0.9 mm steel

Common Applications

- Drywall to steel



DWF

Drywall to Steel Screw


Technical Data

Product Dimensions



References	Head width [mm]	Ø head [mm]	Screw length [mm]	Nb. screw/strip	Nb. screw/box	Compatible tools	Rotation speed [tr/min]	Max rotation speed - DE [U/Min.]	Compatible tools - DE
DWF3925PE	-	-	-	-	-	-	-	-	-
DWF3930PE		-	-	-	-	-	-	-	-
DWF3935PE		-	-	-	-	-	-	-	-
DWF3940PE		-	-	-	-	-	-	-	-
DWF3945PE		-	-	-	-	-	-	-	-

Product Dimensions UK



References	Fastener dimensions [mm]					Qty per Strip	Qty per Box	Recommended RPM	Quik Drive Attachment	Weight [kg]
	d _h	d	l	d ₁	l _g					
DWF3925PE	8.1	3.9	25	2.4	19.5	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWF3930PE		3.9	30	2.4	24.5	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWF3935PE		3.9	35	2.4	29.5	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWF3940PE		3.9	40	2.4	34.5	30	2500	2500 - 6000	QDPR051E / QD76KE	0.002
DWF3945PE		3.9	45	2.4	39.5	30	2000	2500 - 6000	QDPR051E / QD76KE	0.003

DWF

Drywall to Steel Screw



SIMPSON

Strong-Tie®