

Technical data sheet

SIMPSON

Strong-Tie

DWC

Drywall to Timber Screw

The DWC screw is designed for fixing drywall to timber. The screw features a sharp point, coarse thread and bugle head which provides a neat finish in the drywall. The DWC is CE marked to EN14566 and has a grey phosphate coating making it suitable for use indoors.

Features

Material

- Steel - Grey phosphate coating

Benefits

- CE marked to EN14566
- Bugle head
- Sharp point
- Coarse thread
- PH2 driver bits included (BIT2PE)


Applications

Support

- Suitable for fixing to solid wood, composite wood, glued laminate and OSB

Common Applications

- Plasterboard to timber



DWC
Drywall to Timber Screw

Technical Data

Dimensions and characteristics values



References	Head width [mm]	Ø head [mm]	Screw length [mm]	Qty screws / strip	Qty screws / box	Max rotation speed - DE [U/Min.]	Compatible tool	Max rotation speed [tr/min]
DWC3525PE	8.2	3.5	25	30	2500	2500	QDPRO51E / QD76KE	2500
DWC3535PE		3.5	35	30	2500	2500	QDPRO51E / QD76KE	2500
DWC3550PE		3.5	50	30	2000	2500	QDPRO51E / QD76KE	2500

DWC
Drywall to Timber Screw

