

## Technical data sheet

**SIMPSON****Strong-Tie**

BNSP

### BNSP - winbracing system

BNSP clamping device must be permanently mounted and tightened.

## Features

### Material

#### Steel quality:

S 250 GD + Z 275 according to DIN EN 10346

#### Corrosion protection:

275 g / m galvanized on both sides 20mm

- Screws: Quality 8.8

- Trn:

#### Steel quality:

S 235 JR according to EN 10025 DIN

#### Corrosion protection:

Galvanizing layer thickness of about 55 microns in accordance with DIN EN 1461

### Benefits

- Connection tapes with other clamping elements and the subsequent withdrawal.
- When using any screws or pins are the ultimate common connector always more than just connecting tape

## Applications

### Applicable materials

- Fasteners BNK, BNF, BNG

### Application area

- From an economic application of Simpson Strong-Tie bracing belt, there are other products that have been developed for simple solutions to connectivity problems. In summary, the products of this group are called bracing systems
- They are available for the respective widths 25, 40 and 60 mm
- To connect the 80 mm tapes up to 60 items of the system can be used.
- bracing system can be easily clamped by means BNSP or products BNF or BNK BNG (see following pages)
- When turning threaded rods right / left hand, there is another option tension.
- The connection between the connection lugs of the belt is achieved CLIPS20 or CLIPS23 on other products cotter



BNSP

**BNSP - winbracing system**

## Technical Data

Dimensioner



References	DB. nr.	NOB nr.	Dimensions [mm]			Holes			Passende bånd	Medleverede skruer/clips	Båndspænder fastgjort til		Antal pr. kasse	Weight [kg]
			A	B	C	Ø	Venstre (antal)	Højre (antal)			Bånd	BNF: BNG: BNK		
BNSP80-B	8271264	21217146	300-360	80	35	5 + 21	11 + 0	8 + 1	BANxx80xx	2 x BF4060M5; 4 x BF25M5	x	x	4	1.8





BNSP

**BNSP - winbracing system**

## Installation

Installation

- **CLIPS20 bzw. CLIPS23**



BNSP

**BNSP - winbracing system**

