

CLNG

**Kledningspiker, Varmgalvanisert**

*For deg som håndspikrer kledning. Punkterer ikke vindtettingen. Rillet spiker gir best hold. Dimensjoner tilpasset norsk trevirke.*

## Egenskaper


### Fordeler:

- Flatt hode
- 60 graders diamant spids
- Rillet

## Anvendelse

### Bruksområde:


- For vanlig kledning som skal males eller beises
- 48 mm er tilpasset underligger
- 65 mm er tilpasset overligger og liggende kledning



CLNG  
Kledningspiker, Varmgalvanisert

## Teknisk data

### Product dimensions



Art. nr.	Item code	NOBB nr.	Fastener dimensions [mm]						Qty/box
			d	l	d <sub>h</sub>	l <sub>g</sub>	t <sub>fix</sub>	bit	
CLNG2.8x65	75649	55841565	2.8	63.5	6.9	50	41.1	-	500
CLNG2.8x48	75648	55841554		47	6.9	24	24.6	-	1000

### Product characteristic properties

Art. nr.	Product characteristic properties					
	Characteristic Yield Moment – M <sub>y,k</sub> [M <sub>y,k</sub> ] [Nm]	Characteristic withdrawal parameter - f <sub>ax,k,90°</sub> [f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ]	Characteristic head pull-through parameter - f <sub>head,k</sub> [f <sub>head,k</sub> ] [N/mm <sup>2</sup> ]	Characteristic tensile capacity - f <sub>tens,k</sub> [f <sub>tens,k</sub> ] [kN]	Characteristic torsional strength - f <sub>tor,k</sub> [f <sub>tor,k</sub> ] [Nm]	Torsional ratio
CLNG2.8x65	3.2	8.9	29.4	3.4	-	-
CLNG2.8x48	3.2	8.9	29.4	3.4	-	-

