


CSA-ZT

Quik Drive® CSA Beslagskruer Impreg+

Quik Drive® collated CSA connector screw is developed for mounting of steel connectors to timber.

The conical head secures fully contact to the connector which increases the transfer of force. A fixed connection with larger cross-bearing capacity than for standard screws is obtained. The torx helps to fix the screw during insertion.



Egenskaper

Materiale

- Stålkvalitet:
Karbonstål
- Korrosjonsbeskyttelse:
275 g/m² på begge sider – i henhold til en sinklagstykkelse på ca. 20 µm

Fordeler

- The thread is developed for timber and ensures a light and quick running into the timber
- The timber does not crack
- The conical shape under the head allow a full contact of the screw with the hole.
- The Impreg®+ coating allow the use of these screws in outdoor condition

Anvendelse

Skjøter

- **Hovedbjelke/sekunderbjelke:** massivt tre, komposittbjelker, limt laminert tre

Bruksområder

- Innfesting av vinkelbeslag
- Bjelkesko
- Vindtrekkbånd, mv.



CSA-ZT
 Quik Drive® CSA Beslagskruer Impreg+

Teknisk data

Dimensjoner



Art. nr.	NOBB nr.	Dimensjoner [mm]					Antall pr strip	Antall pr eske	Anbefalt RPM	Forsats
		d	l	d _h	l _g	bit				
CSA5.0x35ZT	57302026	5	35	8.3	29	T-20	25	1500	2500-4000	QDBPC50E
CSA5.0x40ZT	57302034	5	40	8.3	34	T-20	25	1500	2500-4000	QDBPC50E

