

Tekniskt datablad

SIMPSON

Strong-Tie

DSPROA4

Hardwood Decking Screw - Stainless Steel A4

Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.

Egenskaper

Material

- Stainless Steel A4

Features:

- 6 lobe drive
- Double threaded
- Chisel point


Användning

Applications:

- Hardwood decking boards to wood

Suitable for:



- Outdoor decking applications



DSPROA4 Hardwood Decking Screw - Stainless Steel A4

Teknisk data

Dimensioner



Art. nr.	Item code	Article number	NOBB	Dimensions [mm]						Bit	Cond.	m ² / box	Box Quantity	Vikt [kg]
				d	l	d _h	d ₁	l _{g1}	l _{g2}					
DSPROA45.5X50	74287	74287	53293777	5.5	50	7	3.8	22.5	10.5	T-25	150	4.4	150	0.005
DSPROA45.5X60	74288	74288	53293781		60	7	3.8	27.5	10.5	T-25	150	4.4	150	0.005
DSPROA45.5X70	74289	74289	53293796		70	7	3.8	32.5	10.5	T-25	150	4.4	150	0.005
DSPROA45.5X80	74290	74290	53293800		80	7	3.8	37.5	10.5	T-25	150	4.4	150	0.006

Product characteristic properties

Art. nr.	Yield Moment $M_{y,k}$ [Nm]	Withdrawal Parameter $f_{ax,k}$ [N/mm ²]	Head Pull Through Parameter $f_{head,k}$ [N/mm ²]	Characteristic Tensile Capacity $f_{tens,k}$ [kN]	Torsional ratio
DSPROA45.5X50	7585	12.8	31.8	7.8	3.8
DSPROA45.5X60	7585	12.8	31.8	7.8	3.8
DSPROA45.5X70	7585	12.8	31.8	7.8	3.8
DSPROA45.5X80	7585	12.8	31.8	7.8	3.8

