

POLY-GP

All round injektionsmassa

Ankarmassa för infästning i murverk och lättbetong.

Egenskaper

Material

- Polyester

Godkännande: ETA-13/0415, DoP-e13/0415

Fördelar

- Snabb montering – tidsbesparande
- Spänningsfri fastsättning
- Reducerade kan- och inbördes avstånd
- Kan även användas inomhus
- Mycket hållbart montage
- Förseglar hålet


Användning

Monteras på

- Murverk
- Lättbetong

Användningsområden

- Stålkonstruktioner
- Skensystem
- Fasader
- Balkar
- Hyllor
- Maskiner, sanitet
- Antenner
- Markiser
- Upphängning av varmvattenberedare och luftkonditioneringsanläggningar



Fixation d'une cloture

POLY-GP
All round injektionsmassa

Teknisk data

Références

Art. nr.	Product information						
	DB nr.	NOBB nr.	Grey color	Beige color	Content [ml]	Weighth [kg]	Packaging qty [pcs]
POLYGP300BG-DK	2099769	56491585	-	-	300	0.586	12

Design resistance – Tension – NRd [kN] – Carbon steel 5.8

Art. nr.	Design resistance – N _{Rd} – Carbon steel 5.8 [kN]							
	Non-cracked concrete							
	h _{ef} = 8d				h _{ef} = 12d			
	C20/25	C30/37	C40/50	C50/60	C20/25	C30/37	C40/50	C50/60
POLY-GP + LMAS M8	4.6	5	5.3	5.5	6.9	7.4	7.9	8.2
POLY-GP + LMAS M12	10	10.9	11.6	12	15.1	16.3	17.3	17.9
POLY-GP + LMAS M16	14.3	15.4	16.4	17	21.4	23.2	24.7	25.5

Concrete :

1. The design loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s). The loading figures are valid for unreinforced concrete and reinforced concrete with a rebar spacing $s \geq 15$ cm (any diameter) or with a rebar spacing $s \geq 10$ cm, if the rebar diameter is 10mm or smaller.
2. The figures for shear are based on a single anchor without influence of concrete edges. For anchorages close to edges ($c \leq \max [10 h_{ef}; 60d]$) the concrete edge failure shall be checked per ETAG 001, Annex C, design method A.
3. Concrete is considered non-cracked when the tensile stress within the concrete is $\sigma_L + \sigma_R \leq 0$. In the absence of detailed verification $\sigma_R = 3$ N/mm² can be assumed (σ_L equals the tensile stress within the concrete induced by external loads, anchors loads included).

POLY-GP
All round injektionsmassa

Design resistance – Tension – N_{Rd} [kN] – Stainless steel A4-70

Art. nr.	Design resistance – N_{Rd} – Stainless steel A4-70 [kN]							
	Non-cracked concrete							
	$h_{ef} = 8d$				$h_{ef} = 12d$			
	C20/25	C30/37	C40/50	C50/60	C20/25	C30/37	C40/50	C50/60
POLY-GP + LMAS M8	4.6	5	5.3	5.5	6.9	7.4	7.9	8.2
POLY-GP + LMAS M12	10	10.9	11.6	12	15.1	16.3	17.3	17.9
POLY-GP + LMAS M16	14.3	15.4	16.4	17	21.4	23.2	24.7	25.5

Concrete :

1. The design loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s). The loading figures are valid for unreinforced concrete and reinforced concrete with a rebar spacing $s \geq 15$ cm (any diameter) or with a rebar spacing $s \geq 10$ cm, if the rebar diameter is 10mm or smaller.
2. The figures for shear are based on a single anchor without influence of concrete edges. For anchorages close to edges ($c \leq \max [10 h_{ef}; 60d]$) the concrete edge failure shall be checked per ETAG 001, Annex C, design method A.
3. Concrete is considered non-cracked when the tensile stress within the concrete is $\sigma_L + \sigma_R \leq 0$. In the absence of detailed verification $\sigma_R = 3$ N/mm² can be assumed (σ_L equals the tensile stress within the concrete induced by external loads, anchors loads included).

Design resistance – Shear – V_{Rd} [kN] – Carbon steel 5.8

Art. nr.	Design resistance – V_{Rd} – Carbon steel 5.8 [kN]							
	Non-cracked concrete							
	$h_{ef} = 8d$				$h_{ef} = 12d$			
	C20/25	C30/37	C40/50	C50/60	C20/25	C30/37	C40/50	C50/60
POLY-GP + LMAS M8	7.2	7.2	7.2	7.2	7.2	7.2	7.2	7.2
POLY-GP + LMAS M12	16.8	16.8	16.8	16.8	16.8	16.8	16.8	16.8
POLY-GP + LMAS M16	31.2	31.2	31.2	31.2	31.2	31.2	31.2	31.2

Concrete :

1. The design loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s). The loading figures are valid for unreinforced concrete and reinforced concrete with a rebar spacing $s \geq 15$ cm (any diameter) or with a rebar spacing $s \geq 10$ cm, if the rebar diameter is 10mm or smaller.
2. The figures for shear are based on a single anchor without influence of concrete edges. For anchorages close to edges ($c \leq \max [10 h_{ef}; 60d]$) the concrete edge failure shall be checked per ETAG 001, Annex C, design method A.
3. Concrete is considered non-cracked when the tensile stress within the concrete is $\sigma_L + \sigma_R \leq 0$. In the absence of detailed verification $\sigma_R = 3$ N/mm² can be assumed (σ_L equals the tensile stress within the concrete induced by external loads, anchors loads included).

POLY-GP
All round injektionsmassa

Design resistance – Shear – V_{Rd} [kN] – Stainless steel A4-70

Art. nr.	Design resistance – V_{Rd} – Stainless steel A4-70 [kN]							
	Non-cracked concrete							
	$h_{ef} = 8d$				$h_{ef} = 12d$			
	C20/25	C30/37	C40/50	C50/60	C20/25	C30/37	C40/50	C50/60
POLY-GP + LMAS M8	8.3	8.3	8.3	8.3	8.3	8.3	8.3	8.3
POLY-GP + LMAS M12	19.2	19.2	19.2	19.2	19.2	19.2	19.2	19.2
POLY-GP + LMAS M16	34.3	34.3	34.3	34.3	35.3	35.3	35.3	35.3

Concrete :

1. The design loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s). The loading figures are valid for unreinforced concrete and reinforced concrete with a rebar spacing $s \geq 15$ cm (any diameter) or with a rebar spacing $s \geq 10$ cm, if the rebar diameter is 10mm or smaller.
2. The figures for shear are based on a single anchor without influence of concrete edges. For anchorages close to edges ($c \leq \max [10 h_{ef}; 60d]$) the concrete edge failure shall be checked per ETAG 001, Annex C, design method A.
3. Concrete is considered non-cracked when the tensile stress within the concrete is $\sigma_L + \sigma_R \leq 0$. In the absence of detailed verification $\sigma_R = 3$ N/mm² can be assumed (σ_L equals the tensile stress within the concrete induced by external loads, anchors loads included).

Design resistance – Bending moment – M_{Rd} [Nm]

Art. nr.	Design resistance – Bending moment – M_{Rd} [Nm]	
	Carbon steel 5.8	Stainless steel A4-70
POLY-GP + LMAS M8	15.2	16.7
POLY-GP + LMAS M12	52.8	59
POLY-GP + LMAS M16	133.6	149.4

Concrete :

1. The design loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s). The loading figures are valid for unreinforced concrete and reinforced concrete with a rebar spacing $s \geq 15$ cm (any diameter) or with a rebar spacing $s \geq 10$ cm, if the rebar diameter is 10mm or smaller.
2. The figures for shear are based on a single anchor without influence of concrete edges. For anchorages close to edges ($c \leq \max [10 h_{ef}; 60d]$) the concrete edge failure shall be checked per ETAG 001, Annex C, design method A.
3. Concrete is considered non-cracked when the tensile stress within the concrete is $\sigma_L + \sigma_R \leq 0$. In the absence of detailed verification $\sigma_R = 3$ N/mm² can be assumed (σ_L equals the tensile stress within the concrete induced by external loads, anchors loads included).

POLY-GP
All round injektionsmassa

Design resistance – hef = 80 mm ($\leq$ M8) or 85 mm ($\geq$ M10) – Carbon steel $\geq$ 4.6 /
Stainless steel $\geq$ A2-70

Art. nr.	Design resistance – Carbon steel $\geq$ 4.6 / stainless steel $\geq$ A2-70			
	$h_{ef} = 80 \text{ mm } (\leq \text{M8}) \text{ or } 85 \text{ mm } (\geq \text{M10})$			
	Tension - N_{Rd} [kN]		Shear - V_{Rd} [kN]	
	Solid Clay Masonry	Hollow Masonry	Solid Clay Masonry	Hollow Masonry
POLY-GP + LMAS M6	1.6	0.8	2.4	0.8
POLY-GP + LMAS M8	1.6	0.8	2.4	0.8
POLY-GP + LMAS M12	1.6	0.8	2.8	0.8

Masonry :

	Compressive strength f_b [N/mm ²]	Bulk density ρ [kg/m ³]
Solid clay masonry	≥ 18	≥ 1600
Hollow masonry	≥ 6	≥ 900

1. The design resistances have been calculated using the partial safety factors for resistances stated in ETA-approval(s).
2. The recommended loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s) and with a partial safety factor for actions of $\gamma_F=1.4$.
3. For combined tension and shear loads or anchor groups and/or in case of edge influence, a calculation acc. TR 054, design method A shall be performed. For details see ETA - assessment(s)
4. Temperature range: -40°C/+40°C ($T_{mlp} = +24^\circ\text{C}$)
5. Coefficient factor β for in situ tests acc. ETAG 029 see ETA-19/0642; Annex C2
6. Displacements under service load see ETA-19/0642; Annex C2 & C3

POLY-GP
All round injektionsmassa

Design resistance – Bending moment – MRd [Nm]

Art. nr.	Design resistance – Bending moment – MRd [Nm]		
	Carbon steel 5.8	Carbon steel 8.8	Stainless steel ≥ A2-70
POLY-GP + LMAS M6	6.4	9.6	7.1
POLY-GP + LMAS M8	15.2	24	16.7
POLY-GP + LMAS M12	52.8	84	59

Masonry :

	Compressive strength f_b [N/mm ²]	Bulk density [kg/m ³]
Solid clay masonry	≥ 18	≥ 1600
Hollow masonry	≥ 6	≥ 900

1. The design resistances have been calculated using the partial safety factors for resistances stated in ETA-approval(s).
2. The recommended loads have been calculated using the partial safety factors for resistances stated in ETA-approval(s) and with a partial safety factor for actions of $\gamma_F=1.4$.
3. For combined tension and shear loads or anchor groups and/or in case of edge influence, a calculation acc. TR 054, design method A shall be performed. For details see ETA - assessment(s)
4. Temperature range: -40°C/+40°C (T_{mlp} = +24°C)
5. Coefficient factor β for in situ tests acc. ETAG 029 see ETA-19/0642; Annex C2
6. Displacements under service load see ETA-19/0642; Annex C2 & C3

Ancorante Chimico Poliestere

Table "Ancorante Chimico Poliestere" cannot be displayed : no references available.

POLY-GP
All round injektionsmassa


Montering

Exponeringstid

Temperatur	-5°C	0°C	5°C	10°C	15°C	20°C	30°C
Arbetstid	25min	15min	12min	8min	7min	4min	2min
Laddningstid	4h	3h	2h30	1h15	55min	30min	20min



Borra hål.



Rengör hålet med stålborste och blåspump (blås x5, borsta x4 och blås x5).



Indsæt en sihylse



Tryck ut massa tills strängen har enhetlig färg.




Stick in pinnbulten med en roterande rörelse och låt massan härda.



Fäst arbetsstycket och dra åt med rekommenderat moment med en kalibrerad momentnyckel.



Borra hål.



Rengör hålet med stålborste och blåspump (blås x5, Fyld hullet 1/2 - 2/3 op med klæbemørtel ved hjælp af pump fra bunden og udad).



Stick in pinnbulten med en roterande rörelse och låt massan härda.



Fäst arbetsstycket och dra åt med rekommenderat moment med en kalibrerad momentnyckel.

Installation parameters – Concrete

Art. nr.	Installation parameters - Concrete					
	Ø drilling [d ₀] [mm]	Max. fixture hole Ø [d _f] [mm]	Drilling depth (8d) [h ₀ =h _{ef} =8d] [mm]	Drilling depth (12d) [h ₀ =h _{ef} =12d] [mm]	Wrench size [SW]	Installation torque [T _{inst}] [Nm]
POLY-GP + LMAS M8	10	9	64	96	13	8
POLY-GP + LMAS M12	14	14	96	144	19	15
POLY-GP + LMAS M16	18	18	128	192	24	25

POLY-GP
All round injektionsmassa

Spacing, edge distances and member thickness – Concrete

Art. nr.	Spacing, edge distance and member thickness - Concrete											
	Effective embedment depth (8d) [h _{ef,8d}] [mm]	Characteristic spacing for h _{ef,8d} [S _{Cr,N}] [mm]	Characteristic edge distance for h _{ef,8d} [c _{Cr,N}] [mm]	Min. member thickness for h _{ef,8d} [h _{min}] [mm]	Effective embedment depth (12d) [h _{ef,12d}] [mm]	Characteristic spacing for h _{ef,12d} [S _{Cr,N}] [mm]	Characteristic edge distance for h _{ef,12d} [c _{Cr,N}] [mm]	Min. member thickness for h _{ef,12d} [h _{min}] [mm]	Min. spacing [S _{min}] [mm]		Min. edge distance [C _{min}] [mm]	
									8d	12d	8d	12d
POLY- GP + LMAS M8	64	192	96	100	96	288	144	126	32	48	32	48
POLY- GP + LMAS M12	96	288	144	126	144	432	216	174	48	72	48	72
POLY- GP + LMAS M16	128	384	192	158	192	576	288	222	64	96	64	96

Installation parameters – Masonry – Solid clay masonry

Art. nr.	Installation parameters - Solid clay masonry			
	Ø drilling $[d_0]$ [mm]	Max. fixture hole Ø $[d_f]$ [mm]	Drilling depth $[h_1]$ [mm]	Installation torque $[T_{inst}]$ [Nm]
POLY-GP + LMAS M6	8	7	85	2
POLY-GP + LMAS M8	10	9	85	2
POLY-GP + LMAS M12	14	14	90	2

Installation parameters – Masonry – Hollow masonry

Art. nr.	Installation parameters - Hollow masonry			
	Ø drilling $[d_0]$ [mm]	Max. fixture hole Ø $[d_f]$ [mm]	Drilling depth $[h_1]$ [mm]	Installation torque $[T_{inst}]$ [Nm]
POLY-GP + LMAS M6	12	7	85	1.5
POLY-GP + LMAS M8	12	9	85	1.5
POLY-GP + LMAS M12	16	14	90	1.5

Spacing, edge distances and member thickness – Masonry – Solid clay masonry

Art. nr.	Spacing, edge distance and member thickness - Solid clay masonry			
	Min. spacing $[S_{min}]$ [mm]			Min. edge distance $[C_{min}]$ [mm]
	$S_{cr,N} = S_{min}$	$S_{cr,N} \parallel = S_{min} \parallel$	$S_{cr,N}^T = S_{min}^T$	$C_{cr,N} = C_{min}$
POLY-GP + LMAS M6	240	-	-	120
POLY-GP + LMAS M8	240	-	-	120
POLY-GP + LMAS M12	255	-	-	127.5

POLY-GP All round injektionsmassa

Spacing, edge distances and member thickness – Masonry – Hollow masonry

Art. nr.	Spacing, edge distance and member thickness - Hollow masonry			
	Min. spacing [S_{min}] [mm]			Min. edge distance [C_{min}] [mm]
	$s_{cr,N} = s_{min}$	$s_{cr,N} \parallel = s_{min} \parallel$	$s_{cr,N}^T = s_{min}^T$	$c_{cr,N} = c_{min}$
POLY-GP + LMAS M6	-	250	120	100
POLY-GP + LMAS M8	-	250	120	100
POLY-GP + LMAS M12	-	250	120	100

